

OXYGEN - oxygen gas
B&J Welding Supply LTD

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

OXYGEN COMPRESSED LABEL

OXYGEN COMPRESSED USP UN 1072 OXYGEN-2 PRODUCED BY AIR LIQUEFACTION. CAS 7782-44-7 17033 (R 04/05)

CONTENTS _____ LITERS _____ CU FT

IN CASE OF EMERGENCY INVOLVING THIS MATERIAL CALL INFOTRAC AT 1-800-535-5053



OXYGEN REFRIGERATED LIQUID LABEL

REFRIGERATED LIQUID OXYGEN REFRIGERATED LIQUID USP UN 1073 OXYGEN-2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION DO NOT CHANGE OR FORCE FIT CONNECTIONS

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. DO NOT GET LIQUID IN EYES ON SKIN OR CLOTHING. FOR LIQUID WITHDRAWAL WEAR FACE SHIELD AND GLOVES. DO NOT DROP. USE SUITABLE HAND TRUCK FOR CONTAINER MOVEMENT. AVOID SPILLS.

IN CASE OF FROSTBITE OBTAIN MEDICAL TREATMENT IMMEDIATELY. CAS 7782-44-7 41533 (R 10/04) IN CASE OF EMERGENCY INVOLVING THIS MATERIAL CALL INFOTRAC AT 1-800-535-5053

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN1073



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, F_{50} only.

Unintended use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin, or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable tied track for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Cylinder temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow prevention device in the piping.
Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.
CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN CERTIFICATE OF ANALYSIS

CERTIFICATE OF ANALYSIS USP OXYGEN PRODUCED BY AIR LIQUEFACTION PROCESS
SUPPLIER B AND J WELDING SUPPLY LTD 203 N LYNN AVE LAMESA TX 79331

ACTUAL ANALYTICAL RESULTS OF PRODUCT _____% TEST METHOD: SERVOMEX
#00572001B SERIAL NO 1914

CUSTOMER _____ SIZE CYLINDER _____ LOT NUMBER _____ NO OF
CYLINDERS _____ TOTAL CYLINDERS SUPPLIED _____ SUPPLIERS
SIGNATURE _____ DATE _____

CERTIFICATE OF ANALYSIS

USP OXYGEN PRODUCED BY AIR LIQUIFICATION PROCESS

SUPPLIER: *B & J WELDING SUPPLY LTD*
203 N. LYNN AVE.
LAMESA TX 79331

ACTUAL ANALYTICAL RESULTS OF PRODUCT _____ %

TEST METHOD: *SERVOMEX #00572001B* SERIAL NO: 1914

CUSTOMER: _____

<u>SIZE CYLINDER:</u>	<u>LOT NUMBER</u>	<u>NO. OF CYLINDERS:</u>
-----------------------	-------------------	--------------------------

_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

TOTAL CYLINDERS FILLED: _____

SUPPLIER'S SIGNATURE: _____

DATE: _____

PRODUCT WARNINGS AND PRECAUTIONS

FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS Rx ONLY. UNINTERRUPTED USE OF HIGH CONCENTRATIONS OF OXYGEN OVER A LONG DURATION WITHOUT MONITORING ITS EFFECT ON OXYGEN CONTENT OF ARTERIAL BLOOD MAY BE HARMFUL. USE ONLY WITH PRESSURE REDUCING EQUIPMENT AND APPARATUS DESIGNED FOR OXYGEN. DO NOT ATTEMPT TO USE ON PATIENTS WHO HAVE STOPPED BREATHING UNLESS USED IN CONJUNCTION WITH RESUSCITATIVE EQUIPMENT.

VIGOROUSLY ACCELERATES COMBUSTION. KEEP OIL AND GREASE AWAY. USE ONLY WITH EQUIPMENT CLEANED FOR OXYGEN SERVICE AND RATED FOR CYLINDER PRESSURE. USE A BACK FLOW PREVENTATIVE DEVICE IN THE PIPING. CLOSE VALVE AFTER EACH USE AND WHEN EMPTY. CYLINDER TEMPERATURE SHOULD NOT EXCEED 52 C (125 F). USE IN ACCORDANCE WITH THE MATERIAL SAFETY DATA SHEET (MSDS). DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN

oxygen gas

Product Information

Product Type

HUMAN PRESCRIPTION DRUG

Item Code (Source)

NDC:67573-0101

Route of Administration	RESPIRATORY (INHALATION)
--------------------------------	--------------------------

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99.5 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:67573-0101-1	414 L in 1 CYLINDER		
2	NDC:67573-0101-2	682 L in 1 CYLINDER		
3	NDC:67573-0101-3	1696 L in 1 CYLINDER		
4	NDC:67573-0101-4	3452 L in 1 CYLINDER		
5	NDC:67573-0101-5	4033 L in 1 CYLINDER		
6	NDC:67573-0101-6	6900 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/01/1977	

Labeler - B&J Welding Supply LTD (016029732)

Registrant - B&J Welding Supply LTD (016029732)

Establishment

Name	Address	ID/FEI	Business Operations
B&J Welding Supply LTD		016029732	manufacture