

**OXYGEN- oxygen gas**  
**Machine & Welding Supply Company dba Arc3 Gases South**

**Oxygen**

OXYGEN, COMPRESSED USP  
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

ARC3 GASES  
1636 Hwy 301 South Dunn, NC 28334  
1700 Chamberlayne Ave. Richmond, VA 23222  
844-534-8021  
NO SMOKING  
NO VAPING



OXYGEN, COMPRESSED USP  
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

ARC3 GASES

1636 Hwy 301 South Dunn, NC 28334

1700 Chamberlayne Ave. Richmond, VA 23222

844-534-8021

NO SMOKING

NO VAPING



OXYGEN, Refrigerated Liquid USP

UN 1073

ARC3 GASES

1636 Hwy 301 South Dunn, NC 28334

1700 Chamberlayne Ave. Richmond, VA 23222

844-534-8021

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING:

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid Spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**DO NOT REMOVE THIS PRODUCT LABEL.**

CAS: 7782-44-7

**NO SMOKING NO VAPING**



<b>OXYGEN</b>			
oxygen gas			
<b>Product Information</b>			
<b>Product Type</b>	PRESCRIPTION ANIMAL DRUG	<b>Item Code (Source)</b>	NDC:49575-011

**Route of Administration** RESPIRATORY (INHALATION)

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	992 mL in 1 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:49575-011-01	103 L in 1 CYLINDER		
2	NDC:49575-011-02	126 L in 1 CYLINDER		
3	NDC:49575-011-03	150 L in 1 CYLINDER		
4	NDC:49575-011-04	198 L in 1 CYLINDER		
5	NDC:49575-011-05	226 L in 1 CYLINDER		
6	NDC:49575-011-06	420 L in 1 CYLINDER		
7	NDC:49575-011-07	588 L in 1 CYLINDER		
8	NDC:49575-011-08	690 L in 1 CYLINDER		
9	NDC:49575-011-09	1133 L in 1 CYLINDER		
10	NDC:49575-011-10	1567 L in 1 CYLINDER		
11	NDC:49575-011-11	2549 L in 1 CYLINDER		
12	NDC:49575-011-12	3160 L in 1 CYLINDER		
13	NDC:49575-011-13	3172 L in 1 CYLINDER		
14	NDC:49575-011-14	6270 L in 1 CYLINDER		
15	NDC:49575-011-15	8510 L in 1 CYLINDER		
16	NDC:49575-011-16	127100 L in 1 CYLINDER		
17	NDC:49575-011-17	141500 L in 1 CYLINDER		
18	NDC:49575-011-18	179803 L in 1 CAN		
19	NDC:49575-011-19	206472 L in 1 CYLINDER		
20	NDC:49575-011-20	16750 L in 1 DEWAR		
21	NDC:49575-011-21	24950 L in 1 DEWAR		
22	NDC:49575-011-22	25650 L in 1 DEWAR		
23	NDC:49575-011-23	29069 L in 1 DEWAR		
24	NDC:49575-011-24	33500 L in 1 DEWAR		
25	NDC:49575-011-25	33620 L in 1 DEWAR		
26	NDC:49575-011-26	37619 L in 1 DEWAR		
27	NDC:49575-011-27	7760 L in 1 CYLINDER		
28	NDC:49575-011-28	2165 L in 1 CYLINDER		
29	NDC:49575-011-29	3137.5 L in 1 CYLINDER		
30	NDC:49575-011-30	3841 L in 1 CYLINDER		

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NADA	NADA141365	06/15/1999	

**Labeler** - Machine & Welding Supply Company dba Arc3 Gases South (065300535)

### **Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Machine & Welding Supply Company dba Arc3 Gases South		065300535	manufacture

### **Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Machine & Welding Supply Company dba Arc3 Gases South		043975085	manufacture

### **Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Machine & Welding Supply Company dba Arc3 Gases South		962288192	manufacture

Revised: 12/2025

Machine & Welding Supply Company dba Arc3 Gases South