

OXYGEN- oxygen gas
Toll Company

Oxygen

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

TOLL COMPANY

3005 NIAGARA LANE N, PLYMOUTH, MN


763-551-5300

www.tollgas.com

NO SMOKING

NO VAPING

CONTENTS: LTRS: CU.FT.



OXYGEN, COMPRESSED USP

UN1072

C.A.S. NO. 7782-44-7

3005 NIAGARA LANE N

PLYMOUTH, MN

763-551-5300

www.tollgas.com

NO SMOKING

NO VAPING

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size Contents Size Contents

M6 170 Liters E 682 Liters

C 248 Liters H 6910 Liters

D 415 Liters Other Liters

**OXYGEN,
COMPRESSED
USP
UN1072**

C.A.S. NO. 7782-44-7

TOLL COMPANY
3005 NIAGARA LANE N
PLYMOUTH, MN
763-551-5300
www.tollgas.com
Employee Owned

**OXYGEN
2**

NO SMOKING
NO OPEN FLAME

⚠ DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT. Use only with equipment designed for oxygen service. Do not repair or use if not certified for repair. Do not use if damaged or if contents are below 22°C (72°F). Read and follow the Safety Data Sheet (SDS) instructions.

⚠ WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size	Contents	Size	Contents
<input type="checkbox"/> M6	170 Liters	<input type="checkbox"/> E	682 Liters
<input type="checkbox"/> C	248 Liters	<input type="checkbox"/> H	6910 Liters
<input type="checkbox"/> D	415 Liters	<input type="checkbox"/> Other	_____ Liters

REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU.FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only

outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

TOLL COMPANY

3005 NIAGARA LANE N

PLYMOUTH, MN

763-551-5300

www.tollgas.com

NO SMOKING

NO VAPING

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073**



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↓
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: _____ LTRS.
DU.FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.
Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE. OXIDIZER.
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.
Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7
DO NOT REMOVE THIS PRODUCT LABEL.

TOLL COMPANY
3005 NIAGARA LANE N
PLYMOUTH, MN
763-551-5300
www.tollgas.com
Employee Owned



OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:82457-004(NDC:82666-001)
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:82457-004-01	180 L in 1 DEWAR; Type 0: Not a Combination Product	12/17/2021	
2	NDC:82457-004-02	8495 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
3	NDC:82457-004-03	7079 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
4	NDC:82457-004-04	671 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
5	NDC:82457-004-05	410 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
6	NDC:82457-004-06	254 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
7	NDC:82457-004-07	169 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205849	12/17/2021	

Labeler - Toll Company (052740669)

Establishment

Name	Address	ID/FEI	Business Operations
Toll Company		052740669	repack(82457-004)