OXYGEN- oxygen gas Toll Company

Oxygen

OXYGEN, COMPRESSED USP

UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentration of oxygen over a long duration, without monitoring the effect of oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS GAS UNDER PRESSURE: MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABÉL

TOLL COMPANY
3005 NIAGARA LANE N, PLYMOUTH, MN
763-551-5300

www.tollgas.com



OXYGEN, COMPRESSED USP UN1072 C.A.S. NO. 7782-44-7 TOLL COMPANY 3005 NIAGARA LANE N PLYMOUTH, MN 763-551-5300

www.tollgas.com

DANGER: MAY CAUSE OR INTENCIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.


Produced by Air Liquefaction

Size Contents Size Contents

M6 170 liters E 682 Liters

C 248 Liters H 6910 Liters

D 415 Liters Other Liters



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU.FT.

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.

Do not handle until safety precautions have been read and understood. Keep and store

away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

TOLL COMPANY

3005 NIAGARA LANE N

PLYMOUTH, MN

763-551-5300

www.tollgas.com



OXYGEN oxygen gas Product Information HUMAN PRESCRIPTION | Item Code | NDC:82457-004(NDC:82666-

Product Type	DRUG	(Source)	001)
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L	

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:82457- 004-01	180 L in 1 DEWAR; Type 0: Not a Combination Product	12/17/2021	
2	NDC:82457- 004-02	8495 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
3	NDC:82457- 004-03	7079 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
4	NDC:82457- 004-04	671 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
5	NDC:82457- 004-05	410 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
6	NDC:82457- 004-06	254 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	
7	NDC:82457- 004-07	169 L in 1 CYLINDER; Type 0: Not a Combination Product	12/17/2021	

Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205849	12/17/2021	

Labeler - Toll Company (052740669)

Establishment			
Name	Address	ID/FEI	Business Operations
Toll Company		052740669	repack(82457-004)

Revised: 11/2024 Toll Company