

OXYGEN- oxygen gas
Machine & Welding Supply Company dba Arc3 Gases South

Oxygen

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUIFACTION

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

PSIG @ 70 degrees F. Size: Liters:

ARC3 GASES 1636 Hwy 301 South . Dunn, NC 28334 844-534-8021



OXYGEN, REFRIGERATED LIQUID USP UN1073 ARC3 GASES OXYGEN 2

1636 Hwy 301 South . Dunn, NC 28334 844-534-8021

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS;

MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. DO NOT REMOVE THIS PRODUCT LABEL.

CAS: 7782-44-7



OXYGEN, COMPRESSED USP UN1072 OXYGEN 2 Content LTRS. CU.FT

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUIFACTION

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the


Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

ARC3 GASES 1636 Hwy 301 South Dunn, NC 28334 844-534-8021

**OXYGEN,
COMPRESSED
USP
UN 1072**

Content _____ LTRS.
CU. FT




WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.


Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.



1636 Hwy 301 South
Dunn, NC 28334
844-534-8021



OXYGEN, COMPRESSED USP

UN1072

B 141 2015

Size Liters PSIG at 70 F

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not

attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.

ARC3 GASES

1636 Hwy 301 South

Dunn, NC 28334

884-534-8021

**OXYGEN,
COMPRESSED
USP
UN 1072**

| | | |
|-----------|---------------|-----------------------|
| 8 Size | 141 Liters | 2015 PSIG at 70° F |
|-----------|---------------|-----------------------|

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.**

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.

ARC3
GASES

1636 Hwy 301 South
Dunn, NC 28334
844-534-8021

OXYGEN, COMPRESSED USP

UN1072

D 420 2015

Size Liters PSIG at 70 F

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

C.A.S. NO. 7782-44-7


DO NOT REMOVE PRODUCT LABEL.

ARC3 GASES

1636 Hwy 301 South

Dunn, NC 28334

884-534-8021



OXYGEN, COMPRESSED USP

UN1072

E 690 2015

Size Liters PSIG at 70 F

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.


Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

C.A.S. NO. 7782-44-7

DO NOT REMOVE PRODUCT LABEL.

ARC3 GASES
 1636 Hwy 301 South
 Dunn, NC 28334
 884-534-8021



OXYGEN

oxygen gas

Product Information

| | | | |
|--------------------------------|--------------------------|---------------------------|---------------|
| Product Type | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:49575-001 |
| Route of Administration | RESPIRATORY (INHALATION) | | |

Active Ingredient/Active Moiety

| Ingredient Name | Basis of Strength | Strength |
|---|-------------------|---------------|
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | OXYGEN | 992 mL in 1 L |

Packaging

| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
|---|------------------|--|----------------------|--------------------|
| 1 | NDC:49575-001-01 | 103 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 2 | NDC:49575-001-02 | 126 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 3 | NDC:49575- | 150 L in 1 CYLINDER; Type 0: Not a Combination | 06/15/1999 | |

| | | | | |
|----|------------------|---|------------|--|
| 3 | 001-03 | Product | 06/15/1999 | |
| 4 | NDC:49575-001-04 | 198 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 5 | NDC:49575-001-05 | 226 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 6 | NDC:49575-001-06 | 420 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 7 | NDC:49575-001-07 | 588 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 8 | NDC:49575-001-08 | 690 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 9 | NDC:49575-001-09 | 1133 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 10 | NDC:49575-001-10 | 1567 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 11 | NDC:49575-001-11 | 2549 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 12 | NDC:49575-001-12 | 3160 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 13 | NDC:49575-001-13 | 3172 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 14 | NDC:49575-001-14 | 6270 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 15 | NDC:49575-001-15 | 8510 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 16 | NDC:49575-001-16 | 127100 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 17 | NDC:49575-001-17 | 141500 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 18 | NDC:49575-001-18 | 179803 L in 1 CAN; Type 0: Not a Combination Product | 06/15/1999 | |
| 19 | NDC:49575-001-19 | 206472 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 20 | NDC:49575-001-20 | 16750 L in 1 DEWAR; Type 0: Not a Combination Product | 06/15/1999 | |
| 21 | NDC:49575-001-21 | 24950 L in 1 DEWAR; Type 0: Not a Combination Product | 06/15/1999 | |
| 22 | NDC:49575-001-22 | 25650 L in 1 DEWAR; Type 0: Not a Combination Product | 06/15/1999 | |
| 23 | NDC:49575-001-23 | 29069 L in 1 DEWAR; Type 0: Not a Combination Product | 06/15/1999 | |
| 24 | NDC:49575-001-24 | 33500 L in 1 DEWAR; Type 0: Not a Combination Product | 06/15/1999 | |
| 25 | NDC:49575-001-25 | 33620 L in 1 DEWAR; Type 0: Not a Combination Product | 06/15/1999 | |
| 26 | NDC:49575-001-26 | 37619 L in 1 DEWAR; Type 0: Not a Combination Product | 06/15/1999 | |
| 27 | NDC:49575-001-27 | 7760 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 28 | NDC:49575-001-28 | 2165 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 29 | NDC:49575-001-29 | 3137.5 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |
| 30 | NDC:49575-001-30 | 3841 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/15/1999 | |

Marketing Information

| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
|--------------------|--|----------------------|--------------------|
| NDA | NDA205767 | 06/15/1999 | |

Labeler - Machine & Welding Supply Company dba Arc3 Gases South (065300535)

Establishment

| Name | Address | ID/FEI | Business Operations |
|---|---------|-----------|------------------------|
| Machine & Welding Supply Company dba Arc3 Gases South | | 043975085 | manufacture(49575-001) |

Establishment

| Name | Address | ID/FEI | Business Operations |
|---|---------|-----------|------------------------|
| Machine & Welding Supply Company dba Arc3 Gases South | | 065300535 | manufacture(49575-001) |

Establishment

| Name | Address | ID/FEI | Business Operations |
|---|---------|-----------|------------------------|
| Machine & Welding Supply Company dba Arc3 Gases South | | 962288192 | manufacture(49575-001) |

Revised: 12/2024

Machine & Welding Supply Company dba Arc3 Gases South