

**OXYGEN- oxygen gas**  
**Bickett Machine and Supply, Inc**

-----  
**Oxygen**

**Oxygen Compressed**

**OXYGEN, COMPRESSED USP UN 1072**

**OXYGEN 2 (R-K14) 114528**

**C.A.S.7782-44-7**

**Manufactured by:**

**BICKETT MACHINE & GAS SUPPLY, INC.**

**1411 ROBINSON AVENUE**

**P.O. BOX 698**

**PORTSMOUTH, OHIO 45662**

**Δ DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. Open valves slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

**DO NOT REMOVE THIS PRODUCT LABEL**

**Δ WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment.

**Produced by Air Liquefaction.**

SIZE	CONTENTS	SIZE	CONTENTS
__ M6	170 Liters	__ E	682 Liters
__ C	248 Liters	__ H	6910 Liters
__ D	415 Liters	__ Other	___ Liters



# OXYGEN, COMPRESSED USP UN 1072



C.A.S. NO. 7782-44-7

Manufactured by:  
**BICKETT MACHINE & GAS SUPPLY, INC.**  
1411 ROBINSON AVENUE  
P.O. BOX 698  
PORTSMOUTH, OHIO 45662



**△ DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. **DO NOT REMOVE THIS PRODUCT LABEL.**

**△ WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size	Contents	Size	Contents
<input type="checkbox"/> M6	170 Liters	<input type="checkbox"/> E	682 Liters
<input type="checkbox"/> C	248 Liters	<input type="checkbox"/> H	6910 Liters
<input type="checkbox"/> D	415 Liters	<input type="checkbox"/> Other	_____ Liters

## Oxygen Shoulder

**OXYGEN, COMPRESSED USP UN 1072**

**OXYGEN 2 (R-K14) 114525**

**USP**

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

**Produced by Air Liquefaction**

CONTENTS:

LTRS: \_\_\_\_\_

WEIGHT \_\_\_ lbs \_\_\_\_\_ oz

Pressure \_\_\_\_\_ (PSIG@ 70°F)

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use.

CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Manufactured by:

**BICKETT MACHINE & GAS SUPPLY, INC.**

1411 Robinson Avenue

P.O. Box 698

Portsmouth, Ohio 45662

740-353-5710

OXYGEN  
COMPRESSED  
USP  
UN1072



(R-K14) 114529

**USP**  
For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, see other medical applications. For all other medical applications, see other medical applications.

Uninterrupted use of high concentrations of oxygen over a long duration without monitoring its effects on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with respiratory equipment.

Produced by Air Liquefaction

**CONTENTS:**  
Lbs \_\_\_\_\_  
Weight \_\_\_\_\_ lbs \_\_\_\_\_ oz \_\_\_\_\_  
Pressure \_\_\_\_\_ (PSIG @ 70°F)

**BICKETT MACHINE & GAS SUPPLY, INC.**  
**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52° C (125° F). Read and follow the Safety Data Sheet (SDS) before use.  
CAS: 7782-44-7

Manufactured by:  
**BICKETT MACHINE & GAS SUPPLY, INC.**  
1411 Robinson Avenue  
P.O. Box 698  
Painesville, Ohio 44062  
740-353-5710



Oxygen Refrigerated Liq Label

# REFRIGERATED LIQUID

**OXYGEN,  
REFRIGERATED  
LIQUID**

**USP**

**UN1073**



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: \_\_\_\_\_ LTRS:   
CU.FT.

**WARNING:** **USP** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**DANGER:** **MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.  
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC  
BURNS OR INJURY.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY  
EXPLODE ON IGNITION OR IMPACT.**

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

Manufactured by:  
**BICKETT MACHINE & GAS SUPPLY, INC.**  
1411 ROBINSON AVENUE  
P.O. BOX 698  
PORTSMOUTH, OHIO 45662



**REFRIGERATED LIQUID**

**OXYGEN, REFRIGERATED LIQUID USP UN1073**

**OXYGEN 2 (R-K14) 114529**

**! ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.!**

**DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: \_\_\_\_\_ LTRS: \_\_\_ CU.FT. \_\_\_

**WARNING:USP** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the *Federal Food, Drug, and Cosmetic Act*.

**Produced by Air Liquefaction.**

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBELS IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID FIRST AID: IF ON SKIN:** Thaw affected parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL**

Manufactured by:

**BICKETT MACHINE & GAS SUPPLY, INC.**

**1411 ROBINSON AVENUE**

**P.O. BOX 698**

**PORTSMOUTH, OHIO 45662**

# REFRIGERATED LIQUID

**OXYGEN,  
REFRIGERATED  
LIQUID**

**USP**

**UN1073**



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: \_\_\_\_\_ LTRS:   
CU.FT.

**WARNING:** **USP** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**DANGER:** **MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.  
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC  
BURNS OR INJURY.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY  
EXPLODE ON IGNITION OR IMPACT.**

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

Manufactured by:  
**BICKETT MACHINE & GAS SUPPLY, INC.**  
1411 ROBINSON AVENUE  
P.O. BOX 698  
PORTSMOUTH, OHIO 45662



**OXYGEN**

oxygen gas

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:65076-101
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:65076-101-01	113 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
2	NDC:65076-101-02	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
3	NDC:65076-101-03	196 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
4	NDC:65076-101-04	248 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
5	NDC:65076-101-05	640 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
6	NDC:65076-101-06	1738 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
7	NDC:65076-101-07	103 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
8	NDC:65076-101-08	150 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
9	NDC:65076-101-09	255 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
10	NDC:65076-101-10	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
11	NDC:65076-101-11	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
12	NDC:65076-101-12	3512 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
13	NDC:65076-101-13	6900 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
14	NDC:65076-101-14	9310 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1999	
15	NDC:65076-101-15	38700 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1999	
16	NDC:65076-101-16	39560 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1999	

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NDA	NDA206023	01/01/1999	

**Labeler** - Bickett Machine and Supply, Inc (004290177)

**Registrant** - Bickett Machine and Supply, Inc (004290177)

**Establishment**

Name	Address	ID/FEI	Business Operations
Bickett Machine and Supply, Inc		004290177	manufacture(65076-101)

Revised: 10/2024

Bickett Machine and Supply, Inc