OXYGEN - oxygen gas OXYGEN - oxygen liquid BGR Enterprises, Inc. dba Penn Oxygen & Supply Company

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

-----

## Oxygen Compressed USP

Enter section text here






OXYGEN, COMPRESSED USP UN1072 OXYGEN 2 17033 (R 04/05)

Contents: LTRS. Cu.Ft

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. RX only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitory it's effect on Oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produce by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen. Service and rated for cylinder pressure. Use a back flow preventative device in the piping. Close valve after each use and when empty. Cylinder

Use a back flow preventative device in the piping. Close valve after each use and when empty. Cylinder temperatures should not exceed 52 degrees C or (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS).

Do not remove this product label. Penn Oxygen and Supply Company 2000 Penn Avenue Jeannette, PA 15644



## T ALWAYS KEEP CUNTAINER IN UPRIGHT PUSITION. I

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND

GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR

IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Close valve after each use and when empty.

Use in accordance with the Material Safety Data Sheet

(MSDS).

FIRST AID:

IN CASE OF FROSTBITE, obtain medical treatment

immediately.

## DO NOT REMOVE THIS PRODUCT LABEL

Enter section text here

OXYGEN, REFRIGERATED LIQUID

UN1073

OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

KEEP OIL, GREASE, AND COMBUSTIBILES AWAY.

USE ONLY WITH EQUIPMENT CLEANED FOR OXYGEN SERVICE.

STORE AND USE WITH ADEQUATE VENTILATION.

DO NOT GET LIQUID IN EYES, ON SKIN, OR CLOTHING.

FOR LIQUID WITHDRAWAL, WEAR FACE SHIELD AND GLOVES.

DO NOT DROP. USE HAND TRUCK FOR CONTAINER MOVEMENT.

AVOID SPILLS. DO NOT WALK ON OR ROLL EQUIPMENT OVER SPILLS.

CLOSE VALVE AFTER EACH USE AND WHEN EMPTY.

USE IN ACCORDANCE WITH THE MATERIAL SAFETY DATA SHEET (MSDS).

FIRST AID: IN CASE OF FROSTBITE, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

#### **OXYGEN**

oxygen gas

Dackaging

Product Informatio	n
--------------------	---

Product Type HUMAN PRESCRIPTION DRUG Item Code (Source) NDC:50558-001

**Route of Administration** RESPIRATORY (INHALATION)

### **Active Ingredient/Active Moiety**

Ingredient Name	Basis of Strength	Strength

**Oxygen** (UNII: S88TT14065) (Oxygen - UNII:S88TT14065) Oxygen 995 mL in 1 L

11.	ackaging			
#	# Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:50558-001-01	4.01 L in 1 CYLINDER		
2	NDC:50558-001-02	4.94 L in 1 CYLINDER		

 2 NDC:50558-001-02
 4.94 L in 1 CYLINDER

 3 NDC:50558-001-03
 8.03 L in 1 CYLINDER

 4 NDC:50558-001-04
 9.08 L in 1 CYLINDER

 5 NDC:50558-001-05
 1.31 L in 1 CYLINDER

 6 NDC:50558-001-06
 2.63 L in 1 CYLINDER

 7 NDC:50558-001-07
 6.58 L in 1 CYLINDER

8 NDC:50558-001-08 4.44 L in 1 CYLINDER
9 NDC:50558-001-09 .72 L in 1 CYLINDER

## **Marketing Information**

Mar Keting Information				
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date	
unapproved medical gas		04/01/1996		

### **OXYGEN**

oxygen liquid

Product Informati	on
-------------------	----

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:50558-002
--------------	-------------------------	--------------------	---------------

Route of Administration RESPIRATORY (INHALATION)

Activo	Ingro	diant//	ctivo	Moiety
ACTIVE	HIPTE	CHE HILLE	MULIVE	violetv

<b>8</b>		
Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

Packaging					
#	Item Code	Package Description	Marketing Start Date	Marketing End Date	
1	NDC:50558-002-01	75.7 L in 1 DEWAR			
2	NDC:50558-002-02	151.4 L in 1 DEWAR			
3	NDC:50558-002-03	227.2 L in 1 DEWAR			
4	NDC:50558-002-04	302.8 L in 1 DEWAR			

<b>Marketing Infor</b>	mation		
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		04/01/1996	

# Labeler - BGR Enterprises, Inc. dba Penn Oxygen & Supply Company (014247332)

Establishment			
Name	Address	ID/FEI	<b>Business Operations</b>
BGR Enterprises, Inc. dba Penn Oxygen & Supply Company		014247332	manufacture

Revised: 11/2009 BGR Enterprises, Inc. dba Penn Oxygen & Supply Company