

OXYGEN- oxygen gas
American Welding & Gas, Inc.

Oxygen

OXYGEN, COMPRESSED – MEDICAL, USP – UN1072

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.
Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheet (SDS) before use.

NO SMOKING
NO VAPING

American Welding & Gas, Inc.
4900 Falls of Neuse Road, Suite 150
Raleigh, NC 27609
800-967-6874

DO NOT REMOVE THIS PRODUCT LABEL.
CAS: 7782-44-7

Cylinder Type Cu. Ft. Liters

H 225 6371

M 111 3143

40 40 1133

E 24 680

D 15 425

B 5 142

C 9 255

OXYGEN, COMPRESSED



UN1072
MEDICAL, USP



American Welding & Gas, Inc.
4900 Falls of Neuse Road, Suite 150
Raleigh, NC 27609
800-967-6874

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.**

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.



NO SMOKING
NO VAPING



DO NOT REMOVE THIS PRODUCT LABEL.
CAS: 7782-44-7

NET CONTENTS CYLINDER TYPE	CU. FT.	LITERS
<input type="checkbox"/> H	225	6371
<input type="checkbox"/> M	111	3143
<input type="checkbox"/> 40	40	1133
<input type="checkbox"/> E	24	680
<input type="checkbox"/> D	15	425
<input type="checkbox"/> B	5	142
<input type="checkbox"/> C	9	255
<input type="checkbox"/>		

AWG-200 V004 (08/21)

OXYGEN, COMPRESSED - MEDICAL, USP - UN1072

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheet (SDS) before use.

NO SMOKING
NO VAPING

American Welding & Gas, Inc.
4900 Falls of Neuse Road, Suite 150
Raleigh, NC 27609
800-967-6874

DO NOT REMOVE THIS PRODUCT LABEL.
CAS: 7782-44-7

Cylinder Type Cu. Ft. Liters

H 225 6371

M 111 3143


40 40 1133

E 24 680

D 15 425

B 5 142

C 9 255



OXYGEN, REFRIGERATED LIQUID USP - UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED GASES MAY EXPLODE ON IGNITION OR IMPACT.

Keep and store away from clothing and other combustible materials.
Keep valves and fittings free from grease and oil.
Use and store only outdoors or in a well-ventilated place.
In case of fire: Stop leak if safe to do so.
Use a back flow preventive device in the piping.
Use only with equipment of compatible materials of construction and rated for cylinder pressure.
Use only with equipment cleaned for oxygen service.
Close valve after each use and when empty.
Protect from sunlight when ambient temperature exceeds 52C (125F).
Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

NO SMOKING / NO VAPING

American Welding & Gas, Inc.
4900 Falls of Neuse Road, Suite 150
Raleigh, NC 27609
800-967-6874



OXYGEN, REFRIGERATED LIQUID USP - UN1073

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation.

For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful.

Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.

COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED GASES MAY EXPLODE ON IGNITION OR IMPACT.

Keep and store away from clothing and other combustible materials.

Keep valves and fittings free from grease and oil.

Use and store only outdoors or in a well-ventilated place.

In case of fire: Stop leak if safe to do so.

Use a back flow preventive device in the piping.

Use only with equipment of compatible materials of construction and rated for cylinder pressure.

Use only with equipment cleaned for oxygen service.

Close valve after each use and when empty.

Protect from sunlight when ambient temperature exceeds 52C (125F).

Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

NO SMOKING / NO VAPING

American Welding & Gas, Inc.

4900 Falls of Neuse Road, Suite 150

Raleigh, NC 27609

800-967-6874

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073**



NET CONTENTS

180 Liters 160 Liters 45 Liters

30 Liters 20 Liters _____ Liters

MEDICAL OXYGEN, USP

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



American Welding & Gas, Inc.
4900 Falls of Neuse Road,
Suite 150
Raleigh, NC 27609
800-567-6874

TWG

NO SMOKING
NO VAPING

AMWG-201
1007

OXYGEN, COMPRESSED USP - UN1072

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheet (SDS) before use.

NO SMOKING
NO VAPING


Coastal Welding Supply, Inc.
6026 Meaux St.
Beaumont, TX 77708
(409) 838-2511

American Welding & Gas, Inc.
4900 Falls of Neuse Road, Suite 150
Raleigh, NC 27609

CONTENTS:
LITERS CU.FT.

DO NOT REMOVE THIS PRODUCT LABEL.

CAS: 7782-44-7



OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation.

For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful.

Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.

COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED GASES MAY EXPLODE ON IGNITION OR IMPACT.

Keep and store away from clothing and other combustible materials.

Keep valves and fittings free from grease and oil.

Use and store only outdoors or in a well-ventilated place.

In case of fire: Stop leak if safe to do so.

Use a back flow preventive device in the piping.

Use only with equipment of compatible materials of construction and rated for cylinder pressure.

Use only with equipment cleaned for oxygen service.

Close valve after each use and when empty.

Protect from sunlight when ambient temperature exceeds 52C (125F).

Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water.
Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7
DO NOT REMOVE THIS PRODUCT LABEL.

NO SMOKING / NO VAPING

Coastal Welding Supply, Inc.
6026 Meaux St.
Beaumont, TX 77708
(409) 838-2511

American Welding & Gas, Inc.
4900 Falls of Neuse Road, Suite 150
Raleigh, NC 27609

REFRIGERATED LIQUID



OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: _____ LTRS. CU.FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7
DO NOT REMOVE THIS PRODUCT LABEL.

COASTAL
WELDING SUPPLY
SPECIALTY GAS
AN AMERICAN COMPANY

American Welding & Gas, Inc.
4900 Falls of Neuse Road,
Suite 150
Raleigh, NC 27609
800-567-6874



NO SMOKING
NO OPEN
FLAMES

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:44076-010
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
---	-----------	---------------------	----------------------	--------------------

1	NDC:44076-010-01	651 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
2	NDC:44076-010-02	396 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
3	NDC:44076-010-03	7957 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
4	NDC:44076-010-04	113 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
5	NDC:44076-010-05	170 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
6	NDC:44076-010-06	198 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
7	NDC:44076-010-07	227 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
8	NDC:44076-010-08	255 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
9	NDC:44076-010-09	283 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
10	NDC:44076-010-10	3511 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
11	NDC:44076-010-11	680 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
12	NDC:44076-010-12	7051 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
13	NDC:44076-010-13	3540 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
14	NDC:44076-010-14	2350 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
15	NDC:44076-010-15	4361 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
16	NDC:44076-010-16	9543 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/1987	
17	NDC:44076-010-17	167890 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/1987	
18	NDC:44076-010-18	31460 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/1987	
19	NDC:44076-010-19	34207 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/1987	
20	NDC:44076-010-20	16084 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/1987	
21	NDC:44076-010-21	129606 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/1987	
22	NDC:44076-010-22	144303 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/1987	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205840	04/01/1987	

Labeler - American Welding & Gas, Inc. (068181965)

Establishment

Name	Address	ID/FEI	Business Operations
------	---------	--------	---------------------

AMERICAN WELDING & GAS, INC.		018834357	manufacture(44076-010)
------------------------------	--	-----------	------------------------

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		079611085	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		080591151	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		086189198	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		096401170	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		116933887	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		118697324	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc. dba Coastal Welding Supply & Specialty Gas		119024311	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		119199574	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		119305817	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		119811490	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		144839798	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		556349694	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		790945369	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		806534954	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		828380738	manufacture(44076-010)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		829720098	manufacture(44076-010)

Revised: 10/2025

American Welding & Gas, Inc.