

CARBON DIOXIDE- carbon dioxide gas
Matheson Tri-Gas, Inc.

Carbon Dioxide

CARBON DIOXIDE USP

UN1013

CONTENTS: LTRS: CU.FT.

Rx only. WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects, and the precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Matheson Tri-Gas Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Return with 25 psig. CAS: 124-38-9


DO NOT REMOVE THIS PRODUCT LABEL.

MATHESON ask... The Gas Professional TM

MATHESON TRI-GAS

150 ALLEN ROAD. BASKING RIDGE, NJ 07920

1-800-416-2505



REFRIGERATED LIQUID

CARBON DIOXIDE, REFRIGERATED LIQUID USP

UN2187

RX ONLY

WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE.

Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. DO NOT change of force fit connections. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Matheson Tri-Gas Safety Data Sheet (SDS) before use.

Do not vent cylinder in confined spaces. Do not enter confined space where gas may be present unless area has been completely ventilated and Carbon Dioxide content is less than one percent or wearing approved air supplied breathing apparatus with a second person present, similarly equipped. Carbon Dioxide is heavier than air and may collect in pits, tank bottoms, low areas, and near the floor. Enter these areas with the same precautions as a confined space.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9

CONTAINER CONTENTS: LTRS: CU FT:

DO NOT REMOVE THIS PRODUCT LABEL.

MATHESON ask... The Gas Professional™

MATHESON TRI-GAS

150 ALLEN ROAD. BASKING RIDGE, NJ 07920

1-800-416-2505



CARBON DIOXIDE USP

UN1013

CONTENTS: LTRS: CU.FT.

Rx only. **WARNING:** Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects, and the precautions to be taken. **WARNING:** CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. Use a back flow preventive

device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Matheson Tri-Gas Safety Data Sheet (SDS) before use. **FIRST AID: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. **IF ON SKIN:** Thaw frosted parts with lukewarm water. **DO not rub affected area.** Get immediate medical advice/attention. Return with 25 psig. CAS: 124-38-9 **DO NOT REMOVE THIS PRODUCT LABEL.**

MATHESON The Gas Professionals

MATHESON TRI-GAS

909 LAKE CAROLYN PKWY. SUITE 1300

IRVING, TEXAS 75039 . 1-800-416-2505



REFRIGERATED LIQUID

CARBON DIOXIDE, REFRIGERATED LIQUID USP

UN2187

Rx ONLY

WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE

RESPIRATION AND HEART RATE.

Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Always keep container in upright position. DO NOT change or force fit connections. Read and follow the Matheson Tri-Gas Safety Data Sheet (SDS) before use.

Do not vent cylinder in confined spaces. Do not enter confined space where gas may be present unless area has been completely vented and Carbon Dioxide content is less than one percent or wearing approved air supplied breathing apparatus with a second person present, similarly equipped. Carbon Dioxide is heavier than air and may collect in pits, tank bottoms, low areas, and near the floor. Enter these areas with the same precautions as a confined space.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9

CONTAINER CONTENTS: LTRS: CU FT:

DO NOT REMOVE THIS PRODUCT LABEL.

MATHESON The Gas Professionals

MATHESON TRI-GAS

909 LAKE CAROLYN PKWY. SUITE 1300

IRVING, TEXAS 75039 . 1-800-416-2505

REFRIGERATED LIQUID

CARBON DIOXIDE, REFRIGERATED LIQUID
USP
UN2187

NON-FLAMMABLE GAS
2

R: ONLY

WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: CONTAINS REFRIGERATED GAS. MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE.

Do not handle until all safety precautions have been read and understood. Avoid breathing gas.

Use and store only outdoors or in a well-ventilated place.

Wear cold resistant gloves, face shield, and eye protection.

Use a back flow preventive device in the piping.

Close cover after each use and when empty.

Use only with equipment rated for similar pressure.

Never put cylinders into unventilated areas of passenger vehicles.

Do not open valve until connected to equipment prepared for use.

Use only equipment of compatible materials of construction.

Always keep container in upright position.

DO NOT change or force fit connections.

Read and follow the **Matheson Tri-Gas Safety Data Sheet (SDS)** before use.

Do not vent cylinder in confined spaces. Do not enter confined spaces where gas may be present unless area has been completely vented and Carbon Dioxide meters in use with the permit or warning approved air supplied breathing apparatus with a second person present, similarly equipped. Carbon Dioxide is heavier than air and may collect in pits, tank bottoms, low areas, and near the floor. Enter these areas with the same precautions as in a confined space.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

IF ON SKIN: Thaw frostbitten parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9 LTRS

CONTAINER CONTENTS: CU FT

DO NOT REMOVE THIS PRODUCT LABEL.

MATHESON
The Gas Professionals
MATHESON TRI-GAS
909 LAKE CAROLYN PKWY • SUITE 1300
IRVING, TEXAS 75039 • 1-800-416-2505 TGM, 809 (10/21)

CARBON DIOXIDE

carbon dioxide gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:55037-402
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
CARBON DIOXIDE (UNII: 142M471B3J) (CARBON DIOXIDE - UNII:142M471B3J)	CARBON DIOXIDE	992 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:55037-402-01	88.7 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
2	NDC:55037-402-02	246.4 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
3	NDC:55037-402-03	369.6 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
4	NDC:55037-402-04	418.88 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
5	NDC:55037-402-05	517.44 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
6	NDC:55037-402-06	640.64 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	

7	NDC:55037-402-07	1059.5 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
8	NDC:55037-402-08	1330.5 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
9	NDC:55037-402-09	1453.7 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
10	NDC:55037-402-10	1724.8 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
11	NDC:55037-402-11	2464 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
12	NDC:55037-402-12	3696 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
13	NDC:55037-402-14	3967.04 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
14	NDC:55037-402-15	4928 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
15	NDC:55037-402-16	5790.4 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
16	NDC:55037-402-17	6160 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
17	NDC:55037-402-18	12320 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
18	NDC:55037-402-19	11827 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
19	NDC:55037-402-20	16016 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
20	NDC:55037-402-21	17987.2 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
21	NDC:55037-402-22	24640 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
22	NDC:55037-402-23	616 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
23	NDC:55037-402-24	7392 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
24	NDC:55037-402-25	8624 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
25	NDC:55037-402-26	9856 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1987	
26	NDC:55037-402-27	95800 L in 1 CONTAINER; Type 0: Not a Combination Product	01/01/1987	
27	NDC:55037-402-28	106670 L in 1 CONTAINER; Type 0: Not a Combination Product	01/01/1987	
28	NDC:55037-402-29	113610 L in 1 CONTAINER; Type 0: Not a Combination Product	01/01/1987	
29	NDC:55037-402-30	130680 L in 1 CONTAINER; Type 0: Not a Combination Product	01/01/1987	
30	NDC:55037-402-31	150250 L in 1 CONTAINER; Type 0: Not a Combination Product	01/01/1987	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA217082	01/01/1987	

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		035676147	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		045200315	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		074768669	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		111249868	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		361608540	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		606686202	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		832779602	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		965760197	manufacture(55037-402)

Establishment

Name	Address	ID/FEI	Business Operations
Matheson Tri-Gas, Inc.		965760387	manufacture(55037-402)