

**OXYGEN - oxygen gas**  
**Southern Gas and Supply of Mississippi, Inc.**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

UN1072

OXYGEN2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempted to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

UN1072

CONTENTS: LTRS. CU.FT.

GAS AND SUPPLY LAUREL, MS 39440

2905 INDUSTRIAL BLVD. 604-649-5889

OXYGEN,  
COMPRESSED  
USP

UN1072



(P-K11) 090674

CAS: 7782-44-7

GAS AND SUPPLY  
2905 INDUSTRIAL BLVD.

LAUREL, MS 39440  
604-649-5889

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS). DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS: LTRS:   
CU.FT.



OXYGEN, COMPRESSED USP

UN1072

OXYGEN2

C.A.S.NO. 7782-44-7

GAS AND SUPPLY

2905 INDUSTRIAL BLVD. LAUREL, MS 39440

604-649-5889

WARNING: HIGH PRESSURE, OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). DO NOT REMOVE THIS PRODUCT LABEL.


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempted to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Size Contents Size Contents

M6 170 Liters E 682 Liters

C 248 Liters H 6910 Liters

**OXYGEN,  
COMPRESSED  
USP  
UN 1072**



**C.A.S. NO. 7782-44-7**

**GAS AND SUPPLY  
2905 INDUSTRIAL BLVD. LAUREL, MS 39440  
604-649-5889**

**1**

**⚠ WARNING: HIGH PRESSURE, OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT.**  
Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. **Use a backflow preventative device in the piping.** Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with **Material Safety Data Sheet (MSDS)**. **DO NOT REMOVE THIS PRODUCT LABEL.**

**⚠ WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**Produced by Air Liquefaction.**

Size	Contents	Size	Contents
<input type="checkbox"/> M6	170 Liters	<input type="checkbox"/> E	682 Liters
<input type="checkbox"/> C	248 Liters	<input type="checkbox"/> H	6910 Liters
<input type="checkbox"/> D	415 Liters	<input type="checkbox"/> Other	_____ Liters

D 415 Liters Other Liters

OXYGEN, REFRIGERATED LIQUID

USP

OXYGEN 2

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

CONTENTS:

LOT #:

**WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with

pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.**

Keep oil, grease and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Do not change or force fit connections. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

GAS AND SUPPLY

2905 INDUSTRIAL BLVD.

LAUREL, MS 39440

# OXYGEN, REFRIGERATED LIQUID

# USP



## UN1073

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

CONTENTS: \_\_\_\_\_

LOT #: \_\_\_\_\_

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING:** EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Do not change or force fit connections.  
Cylinder temperature should not exceed 52°C (125°F).  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the Material Safety Data Sheet (MSDS).

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**GAS AND SUPPLY**  
**2905 INDUSTRIAL BLVD.**  
**LAUREL, MS 39440**  
**604 - 649 - 5889**

1

604-649-5889

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:53991-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

<b>Active Ingredient/Active Moiety</b>		
<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

<b>Packaging</b>				
<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:53991-001-01	198 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
2	NDC:53991-001-02	425 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
3	NDC:53991-001-03	708 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
4	NDC:53991-001-04	3228 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
5	NDC:53991-001-05	3539 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
6	NDC:53991-001-06	6456 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
7	NDC:53991-001-07	7107 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
8	NDC:53991-001-08	7249 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
9	NDC:53991-001-09	7957 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
10	NDC:53991-001-10	8693 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
11	NDC:53991-001-11	9542 L in 1 CYLINDER; Type 0: Not a Combination Product	10/24/2012	
12	NDC:53991-001-12	180 L in 1 DEWAR; Type 0: Not a Combination Product	10/24/2012	
13	NDC:53991-001-13	200 L in 1 DEWAR; Type 0: Not a Combination Product	10/24/2012	

<b>Marketing Information</b>			
<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NDA	NDA205767	10/24/2012	

**Labeler** - Southern Gas and Supply of Mississippi, Inc. (078641186)

<b>Establishment</b>			
<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Southern Gas and Supply of Mississippi, Inc.		078641186	manufacture(53991-001)