

**OXYGEN - oxygen gas**  
**Temple Industrial Welding Supply Co**

**Oxygen**

Refrigerated Liquid

Oxygen,  
Refrigerated  
Liquid  
USP  
UN1073

Oxygen, 2

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use

**FIRST AID: IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

Temple Welding Supply  
2101 Industrial Blvd  
Temple, TX 76704  
254-778-5571

**REFRIGERATED LIQUID**

**OXYGEN,  
REFRIGERATED  
LIQUID**

**UN1073**

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.  
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC  
BURNS OR INJURY.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY  
EXPLODE ON IGNITION OR IMPACT.**

Do not handle until all safety precautions have been read and understood.  
Keep and store away from clothing and other combustible materials.  
Keep valves and fittings free from grease and oil.  
Use and store only outdoors or in a well-ventilated place.  
Wear cold insulating gloves, face shield, and eye protection.  
In case of fire: Stop leak if safe to do so.  
Use a back flow preventive device in the piping.  
Use only with equipment of compatible materials of construction and rated for cylinder pressure.  
Use only with equipment cleaned for oxygen service.  
**DO NOT** change or force fit connections.  
Avoid spills. Do not walk on or roll equipment over spills.  
Close valve after each use and when empty.  
Always keep container in upright position.  
Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID: IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**Temple Welding Supply**  
2101 INDUSTRIAL BLVD  
TEMPLE, TX 76704 • 254-778-5571

45131  
(01/15)

**OXYGEN**  
oxygen gas

**Product Information**

<b>Product Type</b>	PRESCRIPTION ANIMAL DRUG	<b>Item Code (Source)</b>	NDC:11103-011
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:11103-011-12	132749 L in 1 DEWAR		
2	NDC:11103-011-13	142292 L in 1 DEWAR		
3	NDC:11103-011-14	153902 L in 1 DEWAR		

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NADA	NADA141387	01/01/2014	

**Labeler** - Temple Industrial Welding Supply Co (054381074)**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Temple Industrial Welding Supply Co		054381074	manufacture

Revised: 7/2015

Temple Industrial Welding Supply Co