

**OXYGEN- oxygen gas**  
**Quality Air Products Inc**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use on high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

AIR SUPPLY OF NORTH TEXAS

DALLAS, TX 75211

214-337-4761

RETURN WITH 25 PSIG


NO SMOKING

NO VAPING

OX MH 6400 Liters OX E 705 Liters

OX D 425 Liters OX M6 141 Liters

OX CF



OXYGEN, COMPRESSED USP

UN1072

C.A.S. NO. 7782-44-7

AIR SUPPLY OF NORTH TEXAS

DALLAS, TX 75211

214-337-4761

RETURN WITH 25 PSIG

NO SMOKING

NO VAPING

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size Contents Size Contents

M6 170 Liters E 682 Liters

C 248 Liters H 6910 Liters

D 415 Liters Other Liters

**OXYGEN,  
COMPRESSED  
USP  
UN1072**

C.A.S. NO. 7782-44-7

**AIR SUPPLY OF NORTH TEXAS**  
DALLAS, TX 75211  
**214-337-4761**  
RETURN WITH 25 PSIG

**OXYGEN 2**  
(10X10) 999879

**NO SMOKING  
NO TAMPING**

**▲ DANGER:** MAY CAUSE OR INTENSIFY FIRE. EXCEEDS CONTAINING GAS UNDER PRESSURE. MAY BE FLEETING. IRRITANT. Avoid contact with skin and eyes. Avoid contact with clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire, Stop work if safe to do so. Use a hose end wrench to close if the valve. Use only equipment designed for oxygen service. Do not spray valve and connected equipment. Do not use. Do not use above. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet. ©2017 Air Liquide, Inc.

**▲ WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration without monitoring its effect on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size	Contents	Size	Contents
<input type="checkbox"/> M6	170 Liters	<input type="checkbox"/> E	682 Liters
<input type="checkbox"/> C	248 Liters	<input type="checkbox"/> H	6910 Liters
<input type="checkbox"/> D	415 Liters	<input type="checkbox"/> Other	_____ Liters

REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS

CONTENTS: LTRS: CU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.**

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID: IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**AIR SUPPLY OF NORTH TEXAS**

**DALLAS, TX 75211**

**214-337-4761**

**RETURN WITH 25 PSIG**

**NO SMOKING**

**NO VAPING**

# REFRIGERATED LIQUID

OXYGEN,  
REFRIGERATED  
LIQUID  
USP  
UN1073



↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: \_\_\_\_\_ LTRS.   
CU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx required.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**Produced by Air Liquefaction.**

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.  
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC  
BURNS OR INJURY.  
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED  
LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**AIR SUPPLY OF NORTH TEXAS**

DALLAS, TX 75211

**214-337-4761**



## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:63978-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:63978-001-01	141 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1980	
2	NDC:63978-001-02	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1980	
3	NDC:63978-001-03	705 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1980	
4	NDC:63978-	6400 L in 1 CYLINDER; Type 0: Not a Combination	01/01/1980	

4	001-04	Product	01/01/1980	
5	NDC:63978-001-05	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1980	
6	NDC:63978-001-06	240 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1980	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205712	01/01/1980	

**Labeler** - Quality Air Products Inc (557254711)

## Establishment

Name	Address	ID/FEI	Business Operations
QUALITY AIR PRODUCTS INC		557254711	manufacture(63978-001)

## Establishment

Name	Address	ID/FEI	Business Operations
Quality Air Products, Inc.		078505617	manufacture(63978-001)

Revised: 12/2025

Quality Air Products Inc