

OXYGEN- oxygen gas
A OX Welding Supply Company Inc.

Oxygen Labels

OXYGEN, COMPRESSED USP UN1072
PRODUCED BY AIR LIQUEFACTION OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL CONTENTS: LTRS CU. FT.
A-OX WELDING SUPPLY CO. 101 N. HARLEM AVE. . SIOUX FALLS, SD 57104 605-336-1125



OXYGEN, COMPRESSED USP UN1072
PRODUCED BY AIR LIQUEFACTION OXYGEN 2 CONTENTS: LTRS CU. FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with

resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.
DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

A-OX WELDING SUPPLY CO. 101 N. HARLEM AVE. . SIOUX FALLS, SD 57104 605-336-

**OXYGEN,
COMPRESSED
USP
UN1072**



Produced by Air Liquefaction.

CONTENTS: _____

LTRS.
CU. FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



A-OX WELDING SUPPLY CO.

101 N. HARLEM AVE. • SIOUX FALLS, SD 57104

605-336-1125

40033
(R 02/15)

1125

OXYGEN REFRIGERATED LIQUID, USP UN1073 OXYGEN 2
ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction. Keep out of reach of children. Federal law requires that this container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID

OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Lot Number: Contents: Expiration Date: A-OX WELDING SUPPLY CO. 101 N. HARLEM AVE. . SIOUX FALLS, SD 57104 605-336-

OXYGEN
REFRIGERATED LIQUID, USP
UN 1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING
USP
For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.
Produced by Air Liquefaction.
Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.
READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.
CAS: 7782-44-7

DANGER
MAY CAUSE OR INTENSIFY FIRE; COXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.
Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.

FIRST AID
IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
Lot Number:
Contents:
Expiration Date:

A-OX
Welding Supply Co.
101 N. Harlem Avenue • Sioux Falls, SD 57104
605.336.1125

DO NOT REMOVE THIS PRODUCT LABEL

1125

PurityPlus Specialty Gases by A-OX Welding Supply

Oxygen, Compressed

UN 1072

Medical Gas

Oxygen, USP CAS: 7782-44-7

Rx only

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards,

contraindications and side effects and the precautions to be taken.

DANGER CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ACCIDENTLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL

For Medical Use Only.

Ver. 3.95

A-OX Welding Supply

1617 9th Ave. SW.

Watertown, SD, 57201

605.886.4465



Oxygen, Compressed
UN1072

Medical Gas	
Oxygen, USP	CAS: 7782-44-7

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosage, method, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

DANGER: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED; MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ACCIDENTLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL
For Medical Use Only
Ver. 3.95
A-OX Welding Supply
1617 9th Ave. SW
Watertown, SD, 57201
605.886.4465

PurityPlus Specialty Gases by A-OX Welding Supply

Oxygen, Compressed

UN 1072

Medical Gas

Oxygen, USP CAS: 7782-44-7

Rx only

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

DANGER CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ACCIDENTLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL

For Medical Use Only.

Ver. 3.95

A-OX Welding Supply

1205 Fayland Drive N.

Fargo, ND, 58102

701.532.3304



Oxygen, Compressed
UN1072

Medical Gas
Oxygen, USP CAS: 7782-44-7

Re only

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosage, method, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

DANGER: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED; MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.

Do not handle used or empty pressurized tanks, hoses and related equipment. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Use a leak-tight pressure device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment checked for oxygen service. Open valves slowly. Close valves after each use and release energy. Protect from sunlight when ambient temperature exceeds 12 degrees C (55 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ACCIDENTALLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention.

DO NOT REMOVE THIS PRODUCT LABEL.
For Medical Use Only
Ver. 3.95
A-CIX Welding Supply
1205 Raymond Drive N.E.
Fargo, ND 58102
701-632-2354

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:10297-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10297-001-01	8070 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
2	NDC:10297-001-02	7050 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
3	NDC:10297-001-03	4360 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
4	NDC:10297-001-04	2350 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
5	NDC:10297-001-05	3284 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
6	NDC:10297-001-06	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	

7	NDC:10297-001-07	124 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
8	NDC:10297-001-08	164 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
9	NDC:10297-001-09	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
10	NDC:10297-001-10	622 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
11	NDC:10297-001-11	160 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
12	NDC:10297-001-12	196 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
13	NDC:10297-001-13	618893 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205737	01/02/1978	

Labeler - A OX Welding Supply Company Inc. (024372385)

Establishment

Name	Address	ID/FEI	Business Operations
A OX Welding Supply Company Inc.		024372385	manufacture(10297-001)

Establishment

Name	Address	ID/FEI	Business Operations
A-OX WELDING SUPPLY CO., INC.		024390882	relabel(10297-001)

Establishment

Name	Address	ID/FEI	Business Operations
A-OX WELDING SUPPLY CO., INC.		081108358	relabel(10297-001)

Revised: 10/2021

A OX Welding Supply Company Inc.