

**OXYGEN- oxygen gas**  
**FULLERTON WELDING SUPPLY**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Fullerton Welding Supply


25318 South Highway 88, Inola, OK 74036

918-341-8264

CONTENTS:

LTRS:

CU.FT.



## OXYGEN

oxygen gas

### Product Information

|                                |                          |                           |                |
|--------------------------------|--------------------------|---------------------------|----------------|
| <b>Product Type</b>            | HUMAN PRESCRIPTION DRUG  | <b>Item Code (Source)</b> | NDC:42751-1076 |
| <b>Route of Administration</b> | RESPIRATORY (INHALATION) |                           |                |

### Active Ingredient/Active Moiety

| Ingredient Name   | Basis of Strength | Strength      |
|---|-------------------|---------------|
| <b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | OXYGEN            | 990 mL in 1 L |

### Packaging

| # | Item Code        | Package Description                                     | Marketing Start Date | Marketing End Date |
|---|------------------|---|----------------------|--------------------|
| 1 | NDC:42751-1076-1 | 8510 L in 1 CYLINDER; Type 0: Not a Combination Product | 02/06/2008           |                    |
| 2 | NDC:42751-1076-2 | 5270 L in 1 CYLINDER; Type 0: Not a Combination Product | 02/06/2008           |                    |
| 3 | NDC:42751-1076-3 | 3470 L in 1 CYLINDER; Type 0: Not a Combination Product | 02/06/2008           |                    |
| 4 | NDC:42751-1076-4 | 420 L in 1 CYLINDER; Type 0: Not a Combination Product  | 02/06/2008           |                    |
| 5 | NDC:42751-1076-5 | 690 L in 1 CYLINDER; Type 0: Not a Combination Product  | 02/06/2008           |                    |

## Marketing Information

| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
|--------------------|--|----------------------|--------------------|
| NDA                | NDA205865                                | 02/06/2008           |                    |

**Labeler** - FULLERTON WELDING SUPPLY (556832384)

## Establishment

| Name                     | Address | ID/FEI    | Business Operations     |
|--------------------------|---------|-----------|-------------------------|
| FULLERTON WELDING SUPPLY |         | 556832384 | manufacture(42751-1076) |

Revised: 11/2024

FULLERTON WELDING SUPPLY