

**OXYGEN- oxygen gas**  
**Youngstown Oxygen & Welding Supply, Inc.**

-----  
**Oxygen - 123**

**OXYGEN, COMPRESSED product label**

**OXYGEN, COMPRESSED USP UN 1072 OXYGEN 2 (R-K14A)**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.****DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL.**

CONTENTS:

LTRS: \_\_\_\_

CU.FT. \_\_\_\_


**YOUNGSTOWN OXYGEN & WELDING SUPPLY**

2208 Hubbard Road • Youngstown, OH 4505

**330-744-0271**

OXYGEN,  
COMPRESSED  
USP

UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE. OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store only outdoors or in a well-ventilated place. In case of fire, Stop valves and fittings free from grease and oil. Use and store away from clothing and other combustible materials. Keep leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of combustible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52° C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL


YOUNGSTOWN OXYGEN & WELDING SUPPLY  
2208 Hubbard Road • Youngstown, OH 44505  
330-744-0271

CONTENTS:  
LTRS:   
CU.FT.



OXYGEN,  
COMPRESSED  
USP

UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE. OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store only outdoors or in a well-ventilated place. In case of fire, Stop valves and fittings free from grease and oil. Use and store away from clothing and other combustible materials. Keep leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of combustible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52° C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

YOUNGSTOWN OXYGEN & WELDING SUPPLY  
2208 Hubbard Road • Youngstown, OH 44505  
330-744-0271

CONTENTS:  
LTRS:   
CU.FT.



## OXYGEN

oxygen gas

### Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:54316-123
Route of Administration	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	.995 L in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:54316-123-01	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	

2	NDC:54316-123-02	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
3	NDC:54316-123-03	3455 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
4	NDC:54316-123-04	7839 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
5	NDC:54316-123-05	9537 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	
6	NDC:54316-123-06	1 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/2000	
7	NDC:54316-123-07	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2000	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/2000	

**Labeler** - Youngstown Oxygen & Welding Supply, Inc. (147963755)

**Registrant** - Youngstown Oxygen & Welding Supply, Inc. (147963755)

## Establishment

Name	Address	ID/FEI	Business Operations
Youngstown Oxygen & Welding Supply, Inc.		147963755	manufacture(54316-123)

Revised: 10/2024

Youngstown Oxygen & Welding Supply, Inc.