

OXYGEN- oxygen gas
ACUTE CARE GAS LLC

Oxygen

Oxygen

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2



DANGER: COMPRESSED, OXIDING GAS. MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications. Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure. Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects free of oil and grease to avoid ignition Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 52OC/125OF. Use a back-flow preventative device in the piping. Federal law requires that the container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Use only in accordance with product instructions and material safety data sheet. Keep and store away from heat/sparks/open flame/combustible materials. No smoking. Store and use in a cool, well ventilated place.

DO NOT REMOVE THIS LABEL CAS 7782-44-7

Size & Contents

M6 C / M9 D E H Other

170 Liters 248 Liters 415 Liters 682 Liters 6910 Liters ____Liters

☐ ☐ ☐ ☐ ☐ ☐

Acute Care Gases II, LLC

25 Walker Way 2c

Albany, NY 12205

855-399-1224

**OXYGEN,
COMPRESSED USP
UN 1072**

DANGER:

COMPRESSED, OXIDIZING GAS.
MAY CAUSE OR INTENSIFY FIRE;
OXIDIZER, CONTAINS GAS UNDER
PRESSURE; MAY EXPLODE IF HEATED.



For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: **Rx ONLY.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure. Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects free of oil and grease to avoid ignition. Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 52°C/125°F. Use a back flow preventative device in the piping. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Use only in accordance with product instructions and material safety data sheet. Keep and store away from heat/sparks/open flame/combustible materials. No Smoking. Store and use in a cool, well ventilated place.

DO NOT REMOVE THIS LABEL

CAS NO: 7782-44-7

Size & Contents	M6	C / M9	D	E	H	Other
	170 Liters	248 Liters	415 Liters	682 Liters	6910 Liters	____ Liters
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Acute Care Gases II, LLC

25 Walker Way 2c

Albany, NY 12205

855-399-1224

Oxygen Refridgerated

OXYGEN, REFRIGERATED LIQUID USP UN1073

OXYGEN, U.S.P.

OXYGEN 2



Contents _____ Liters

CAS NO: 7782-44-7

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBELS IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment. Produced by Air Liquefaction

©Applied Home Healthcare Equipment 2014

Acute Care Gases of CT LLC

23 Nutmeg Valley Road

Wolcott, CT 06716

855-399-1224

OXYGEN, REFRIGERATED LIQUID USP

UN 1073



CONTENTS: _____ LITERS

CAS NO: 7782-44-7

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.



Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

©Applied Home Healthcare Equipment 2014

Acute Care Gases of CT LLC
23 Nutmeg Valley Road
Wolcott, CT 06716
855-399-1224

Oxygen 15 Cubic Feet

OXYGEN, COMPRESSED USP UN 1072 Produced by Air Liquefaction



OXYGEN 2 133445 (06/19)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not

attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT



REMOVE THIS PRODUCT LABEL.

CONTENTS: 15 CUBIC FEET

ACG ACUTE CARE GASES OF CT, LLC

ACUTE CARE 23 NUTMEG VALLEY RD • WOLCOTT, CT 06716

GASES 855-399-1224



Oxygen 24 cubic feet

OXYGEN, COMPRESSED USP UN 1072 Produced by Air Liquefaction

217359



OXYGEN 2 133445 (05/25)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without

monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.



CONTENTS: 24 CUBIC FEET

ACG ACUTE CARE GAS, LLC


23 NUTMEG VALLEY RD • WOLCOTT, CT 06716

855-399-1224

NO SMOKING

NO VAPING

**OXYGEN,
COMPRESSED
USP**
UN1072
PRODUCED BY AIR LIQUEFACTION



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **is required.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

ACG ACUTE CARE GASES
ACUTE CARE GAS, LLC
23 NUTMEG VALLEY RD • WOLCOTT, CT 06716
855-399-1224

133445 (05/25)

CONTENTS: 24 CUBIC FEET
NO SMOKING
NO VAPING

Oxygen Compressed - Wolcott

OXYGEN, COMPRESSED USP UN1072

OXYGEN 2



DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER, CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS LABEL

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications. Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

© Applied Home Healthcare Equipment 2014

CAS 7782-44-7

Contents

Size

113 Liters

☐ M4

165 Liters

☐ M6

255 Liters

☐ C

425 Liters

☐ D

680 Liters

☐ E

7080 Liters

☐ H

_____ Liters

☐ Other

Acute Care Gases of CT, LLC

23 Nutmeg Valley Road

Wolcott, CT 06716

855-399-1224

OXYGEN, COMPRESSED USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.



Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction, ©Applied Home Healthcare Equipment 2014

Contents	Size
113 Liters	<input type="checkbox"/> M4
165 Liters	<input type="checkbox"/> M6
255 Liters	<input type="checkbox"/> C
425 Liters	<input type="checkbox"/> D
680 Liters	<input type="checkbox"/> E
7080 Liters	<input type="checkbox"/> H
____ Liters	<input type="checkbox"/> Other

Acute Care Gases of CT, LLC
23 Nutmeg Valley Road
Wolcott, CT 06716
855-399-1224

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:69240-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:69240-001-07	170 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
2	NDC:69240-001-08	248 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
3	NDC:69240-001-09	415 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
4	NDC:69240-001-10	682 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
5	NDC:69240-001-11	6910 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	
6	NDC:69240-001-12	425 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/2014	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	09/01/2014	

Labeler - ACUTE CARE GAS LLC (119338694)

Establishment

Name	Address	ID/FEI	Business Operations
ACUTE CARE GAS LLC		119338694	manufacture(69240-001)

Establishment

Name	Address	ID/FEI	Business Operations
ACUTE CARE GAS LLC		129243310	manufacture(69240-001)

Establishment

Name	Address	ID/FEI	Business Operations
-------------	----------------	---------------	----------------------------

ACUTE CARE GAS LLC		119401481	manufacture(69240-001)
--------------------	--	-----------	------------------------

Establishment			
Name	Address	ID/FEI	Business Operations
ACUTE CARE GAS LLC		085559764	manufacture(69240-001)

Revised: 6/2025

ACUTE CARE GAS LLC