

**OXYGEN- oxygen gas**  
**Volunteer Welding Supply Inc**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

VOLUNTEER WELDING

815 REP JOHN LEWIS WAY SOUTH NASHVILLE, TN 37203 615-256-5658

1000 HEISKELL AVE KNOXVILLE, TN 37921 865-522-8350

502 SOUTH POLK TULLAHOMA, TN 37388 931-454-2646

Main: (615) 256-5658

NO SMOKING

NO VAPING

CONTENTS: LTRS: CU.FT.



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected

area. Get immediate medical help.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

VOLUNTEER WELDING

815 REP JOHN LEWIS WAY SOUTH NASHVILLE, TN 37203 615-256-5658

1000 HEISKELL AVE KNOXVILLE, TN 37921 865-522-8350

502 SOUTH POLK TULLAHOMA, TN 37388 931-454-2646

Main: (615) 256-5658

NO SMOKING

NO VAPING

**REFRIGERATED LIQUID**

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP  
UN1073**



**1 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. 1  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: \_\_\_\_\_ LTRS:   
DU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx required.**  
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.  
**Produced by Air Liquefaction.**

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.  
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.  
COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.  
Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**



815 REP JOHN LEWIS WAY SOUTH • NASHVILLE, TN 37203 • 615-256-5658  
1000 HEISKELL AVENUE • KNOXVILLE, TN 37921 • 865-522-8350  
502 SOUTH POLK • TULLAHOMA, TN 37388 • 931-454-2646  
Main: (615) 256-5658



## OXYGEN

oxygen gas

### Product Information

**Product Type**

HUMAN PRESCRIPTION DRUG

**Item Code (Source)**

NDC:53511-001

**Route of Administration** RESPIRATORY (INHALATION)**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:53511-001-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
2	NDC:53511-001-02	248 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
3	NDC:53511-001-03	426 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
4	NDC:53511-001-04	675 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
5	NDC:53511-001-05	3450 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
6	NDC:53511-001-06	6896 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
7	NDC:53511-001-07	7800 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
8	NDC:53511-001-08	145000 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1973	
9	NDC:53511-001-09	155000 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1973	
10	NDC:53511-001-10	172000 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1973	
11	NDC:53511-001-11	185000 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1973	
12	NDC:53511-001-12	200000 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1973	
13	NDC:53511-001-13	227000 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1973	
14	NDC:53511-001-14	420 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
15	NDC:53511-001-15	690 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
16	NDC:53511-001-16	3454 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
17	NDC:53511-001-17	6909 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
18	NDC:53511-001-18	8495 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
19	NDC:53511-001-19	180 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
20	NDC:53511-001-20	185 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
21	NDC:53511-001-21	190 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
22	NDC:53511-001-22	195 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
23	NDC:53511-001-23	200 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205889	01/01/1973	

**Labeler** - Volunteer Welding Supply Inc (065836520)

**Registrant** - Volunteer Welding Supply Inc (065836520)

## Establishment

Name	Address	ID/FEI	Business Operations
Volunteer Welding Supply Inc		065836520	manufacture(53511-001)

## Establishment

Name	Address	ID/FEI	Business Operations
VOLUNTEER WELDING SUPPLY, INC.		118794231	manufacture(53511-001)

## Establishment

Name	Address	ID/FEI	Business Operations
Volunteer Welding Supply Inc		624758439	manufacture(53511-001)

Revised: 11/2025

Volunteer Welding Supply Inc