

CARBON DIOXIDE- carbon dioxide gas
MITCHELL WELDING SUPPLY

Carbon Dioxide

CARBON DIOXIDE USP

UN1013

Rx Only. WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9 DO NOT REMOVE THIS PRODUCT LABEL.

3539 Highway 271

Tyler, TX 75708


903-593-7343

www.mitchellwelding.com

MWS

Mitchell Welding Supply

CONTENTS: LTRS: CU.FT.



CARBON DIOXIDE

REFRIGERATED LIQUID USP

UN2187

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

Rx ONLY. Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. **WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE.** Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. **DO NOT** change or force fit connections.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.

CAS: 124-38-9

FIRST AID

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

3539 Highway 271

Tyler, TX 75708

903-593-7343

MWS

Mitchell Welding Supply

www.mitchellwelding.com

DBG-COISP-MWY-PK25 2-10-25

CARBON DIOXIDE REFRIGERATED LIQUID USP UN2187



ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

Rx ONLY. Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. **WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE.** Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. DO NOT change or force fit connections.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.
CAS: 124-38-9

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.



3539 Highway 271
Tyler, TX 75708
903-593-7343

MWS
Mitchell Welding Supply
www.mitchellwelding.com



DO NOT REMOVE THIS PRODUCT LABEL

PRINTED BY RATERMANN MFG., INC.
www.rtmorder.com

CARBON DIOXIDE USP

UN1013

WARNING: Rx ONLY. Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated

for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9

DO NOT REMOVE THIS PRODUCT LABEL.

3539 Highway 271

Tyler, TX 75708

903-593-7343

MWS

Mitchell Welding Supply

www.mitchellwelding.com

CARBON DIOXIDE USP

UN1013

NON-FLAMMABLE GAS

2

IP-A338 11152008

WARNING: **Rx ONLY.** Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Wear protective gloves, protective clothing, and either eye or face protection. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 124-38-9

DO NOT REMOVE THIS PRODUCT LABEL.

3539 Highway 271
Tyler, TX 75708
903-593-7343

MWS
Mitchell Welding Supply
www.mitchellwelding.com

CARBON DIOXIDE, REFRIGERATED LIQUID USP

UN2187

MWS

Mitchell Welding Supply

3539 Highway 271

Tyler, TX 75708

903-593-7343

www.mitchellwelding.com

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING:

USP Rx Only. Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Never put cylinders into unventilated areas of passenger vehicles. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. DO NOT change or force fit connections. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

CAS: 124-38-9



CARBON DIOXIDE

carbon dioxide gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:72276-004
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
CARBON DIOXIDE (UNII: 142M471B3J) (CARBON DIOXIDE - UNII:142M471B3J)	CARBON DIOXIDE	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:72276-004-01	16055 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
2	NDC:72276-004-02	18183 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
3	NDC:72276-004-03	1745 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
4	NDC:72276-004-04	14169 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	
5	NDC:72276-004-05	18609 L in 1 CYLINDER; Type 0: Not a Combination Product	05/13/2025	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA220461	05/13/2025	

Labeler - MITCHELL WELDING SUPPLY (047833462)**Establishment**

Name	Address	ID/FEI	Business Operations
MITCHELL WELDING SUPPLY		047833462	manufacture(72276-004)

Establishment

Name	Address	ID/FEI	Business Operations
Mitchell Welding Supply		118920889	manufacture(72276-004)

Revised: 11/2025

MITCHELL WELDING SUPPLY