

OXYGEN- oxygen gas
T.W. Smith Corp.

Oxygen - 005

OXYGEN, COMPRESSED USP
UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

T.W. SMITH

885 Meeker Avenue, Brooklyn, NY 11222

718-388-7417

OXYGEN,
COMPRESSED
USP
UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

T.W. SMITH
885 Meeker Avenue, Brooklyn, NY 11222
718 - 388 - 7417



REFRIGERATED LIQUID
OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

T.W. SMITH

885 Meeker Avenue, Brooklyn, NY 11222

718-388-7417



OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:52563-005
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:52563-005-01	6270 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
2	NDC:52563-005-02	3841 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
3	NDC:52563-005-03	2165 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
4	NDC:52563-005-04	1724 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
5	NDC:52563-005-05	420 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
6	NDC:52563-005-06	690 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	

7	NDC:52563-005-07	150 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
8	NDC:52563-005-08	113267 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
Marketing Information				
Marketing Category		Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA		NDA205849	01/01/1976	

Labeler -
T.W. Smith Corp. (001853126)

Establishment			
Name	Address	ID/FEI	Business Operations
T.W. SMITH CORP.		001853126	manufacture(52563-005)