


OXYGEN- oxygen gas
New Bedford Welding Supply, Inc.

Oxygen

OXYGEN, COMPRESSED USP UN1072 PRODUCED BY AIR LIQUEFACTION OXYGEN2
WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.
CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL. CONTENTS: LTRS CU. FT.
NEW BEDFORD WELDING SUPPLY, INC.
286 HERMAN MELVILLE BLVD. NEW BEDFORD, MA 02740 . 508-997-2051



| OXYGEN | | | |
|-------------------------|--------------------------|--------------------|---------------|
| oxygen gas | | | |
| Product Information | | | |
| Product Type | PRESCRIPTION ANIMAL DRUG | Item Code (Source) | NDC:23650-011 |
| Route of Administration | RESPIRATORY (INHALATION) | | |

| Active Ingredient/Active Moiety | | |
|---|-------------------|---------------|
| Ingredient Name | Basis of Strength | Strength |
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | OXYGEN | 990 mL in 1 L |

| Packaging | | | | |
|-----------|------------------|----------------------|----------------------|--------------------|
| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
| 1 | NDC:23650-011-01 | 387 L in 1 CYLINDER | | |
| 2 | NDC:23650-011-02 | 643 L in 1 CYLINDER | | |
| 3 | NDC:23650-011-03 | 5324 L in 1 CYLINDER | | |
| 4 | NDC:23650-011-04 | 6400 L in 1 CYLINDER | | |
| 5 | NDC:23650-011-05 | 7051 L in 1 CYLINDER | | |
| 6 | NDC:23650-011-06 | 3172 L in 1 CYLINDER | | |
| 7 | NDC:23650-011-07 | 3511 L in 1 CYLINDER | | |
| 8 | NDC:23650-011-08 | 90 L in 1 CYLINDER | | |
| 9 | NDC:23650-011-09 | 141 L in 1 CYLINDER | | |
| 10 | NDC:23650-011-10 | 198 L in 1 CYLINDER | | |
| 11 | NDC:23650-011-11 | 234 L in 1 CYLINDER | | |
| 12 | NDC:23650-011-12 | 547 L in 1 CYLINDER | | |
| 13 | NDC:23650-011-13 | 1738 L in 1 CYLINDER | | |
| 14 | NDC:23650-011-14 | 578 L in 1 CYLINDER | | |
| 15 | NDC:23650-011-15 | 7221 L in 1 CYLINDER | | |
| 16 | NDC:23650-011-16 | 7929 L in 1 CYLINDER | | |
| 17 | NDC:23650-011-17 | 8552 L in 1 CYLINDER | | |
| 18 | NDC:23650-011-18 | 9401 L in 1 CYLINDER | | |

| Marketing Information | | | |
|-----------------------|--|----------------------|--------------------|
| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
| NADA | NADA141365 | 01/01/2006 | |

Labeler - New Bedford Welding Supply, Inc. (050319714)

| Establishment | | | |
|----------------------------------|---------|-----------|---------------------|
| Name | Address | ID/FEI | Business Operations |
| New Bedford Welding Supply, Inc. | | 050319714 | manufacture |

Revised: 10/2024

New Bedford Welding Supply, Inc.