

OXYGEN- oxygen gas
Metro Welding Supply Corporation

oxygen

OXYGEN, REFRIGERATED LIQUID USP
UN1073

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. DANGER: MAY CAUSE OR INENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Always keep container in upright position. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Read and follow the Safety Data Sheet (SDS) before use. FIRST AIR: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

METRO WELDING SUPPLY
12620 SOUTHFIELD DETROIT, MI 48223
CALL (313) 834-1660 FOR PICKUP
NO SMOKING
NO VAPING



OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

METRO WELDING SUPPLY

12620 SOUTHFIELD DETROIT, MI 48223

CALL (313) 834-1660 FOR PICKUP

NO SMOKING

NO VAPING



OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:62273-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:62273-011-01	113 L in 1 CYLINDER		
2	NDC:62273-011-02	170 L in 1 CYLINDER		
3	NDC:62273-011-03	255 L in 1 CYLINDER		
4	NDC:62273-011-04	425 L in 1 CYLINDER		
5	NDC:62273-011-05	680 L in 1 CYLINDER		
6	NDC:62273-011-06	1274 L in 1 CYLINDER		
7	NDC:62273-011-07	3540 L in 1 CYLINDER		
8	NDC:62273-011-08	7108 L in 1 CYLINDER		
9	NDC:62273-011-09	160 L in 1 DEWAR		
10	NDC:62273-011-10	180 L in 1 DEWAR		
11	NDC:62273-011-11	240 L in 1 DEWAR		
12	NDC:62273-011-12	230 L in 1 DEWAR		
13	NDC:62273-011-13	40698 L in 1 DEWAR		

14	NDC:62273-011-14	45 L in 1 DEWAR		
15	NDC:62273-011-15	1000 L in 1 CYLINDER		
16	NDC:62273-011-16	1500 L in 1 CYLINDER		
17	NDC:62273-011-17	2000 L in 1 CYLINDER		
18	NDC:62273-011-18	3000 L in 1 CYLINDER		
19	NDC:62273-011-19	200 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141387	01/01/1980	

Labeler - Metro Welding Supply Corporation (005328869)

Establishment

Name	Address	ID/FEI	Business Operations
Metro Welding Supply Corporation		005328869	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
Metro Welding Supply Corporation		079716147	manufacture

Revised: 10/2025

Metro Welding Supply Corporation