OXYGEN- oxygen gas Gulf Coast Gas & Equipment, LLC

Oxygen

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

MERITUS TEXAS

11924 N. Houston-Rosslyn Road


Houton, Texas 77086

www.gulfcoastgastx.com

NO SMOKING

NO VAPING

CONTENTS: LRTS: CU.FT



OXYGEN COMPRESSED, USP

UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or with adequate ventilation. Store in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL.

CAS: 7782-44-7

MERITUS TEXAS


11924 N. Houston-Rosslyn Road

Houton, Texas 77086

www.gulfcoastgastx.com

NO SMOKING

NO VAPING



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS: CU.FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Obtain, read and follow all safety instructions before use. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of

compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Do not open valve until connected to equipment prepared for use. Open valve slowly. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical help.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

MERITUS TEXAS


11924 N. Houston-Rosslyn Road

Houton, Texas 77086

www.gulfcoastgastx.com

NO SMOKING

NO VAPING



OXYGEN

oxygen gas

| Product Information | | | |
|-------------------------|--------------------------|--------------------|---------------|
| Product Type | HUMAN PRESCRIPTION DRUG | Item Code (Source) | NDC:85812-001 |
| Route of Administration | RESPIRATORY (INHALATION) | | |

| Active Ingredient/Active Moiety | | |
|---|-------------------|---------------|
| Ingredient Name | Basis of Strength | Strength |
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | OXYGEN | 990 mL in 1 L |

| Packaging | | | | |
|-----------|----------------------|---|-------------------------|-----------------------|
| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
| 1 | NDC:85812- 001-01 | 420 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/30/2025 | |
| 2 | NDC:85812- 001-02 | 690 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/30/2025 | |
| 3 | NDC:85812- 001-03 | 3470 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/30/2025 | |
| 4 | NDC:85812- 001-04 | 7060 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/30/2025 | |
| 5 | NDC:85812- 001-05 | 8510 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/30/2025 | |
| 6 | NDC:85812- 001-06 | 180 L in 1 CYLINDER; Type 0: Not a Combination Product | 06/30/2025 | |

| Marketing Information | | | |
|-----------------------|---|-------------------------|-----------------------|
| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
| NDA | NDA205767 | 06/30/2025 | |
| | | | |

Labeler - Gulf Coast Gas & Equipment, LLC (067395514)

| Establishment | | | |
|---------------------------------|---------|-----------|----------------------------|
| Name | Address | ID/FEI | Business Operations |
| Gulf Coast Gas & Equipment, LLC | | 067395514 | manufacture(85812-001) |

Revised: 11/2025 Gulf Coast Gas & Equipment, LLC