

OXYGEN- oxygen gas
- INDUSTRIAL WELDING SUPPLY CO. OF HARVEY, INC.

Oxygen

OXYGEN, COMPRESSED USP

UN 1072

OXYGEN2

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7. DO NOT REMOVE THIS PRODUCT LABEL.

IWS Gas and Supply


111 Buras Drive

Belle Chasse, LA 70037

(504) 392-2400

CONTENTS: LTRS.

CU.FT.



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS. CU.FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

IWS GAS AND SUPPLY

111 Buras Drive

Belle Chasse, LA 70037

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN1073



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: _____

LTRS: ☐

CU FT: ☐

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52°C (125°F)

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the **Material Safety Data Sheet (MSDS)**.

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.
CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



111 Buras Drive
Belle Chasse, LA 70037
(504)392-2400

47136
(R 10/05)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42241-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42241-001-01	198 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
2	NDC:42241-001-02	425 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
3	NDC:42241-001-03	708 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
4	NDC:42241-001-04	3228 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
5	NDC:42241-001-05	3539 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
6	NDC:42241-001-06	6371 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
7	NDC:42241-001-07	7107 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
8	NDC:42241-001-08	7249 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
9	NDC:42241-001-09	7957 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
10	NDC:42241-001-10	8693 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
11	NDC:42241-001-11	9543 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2011	
12	NDC:42241-001-12	180 L in 1 DEWAR; Type 0: Not a Combination Product	11/01/2011	
13	NDC:42241-001-13	200 L in 1 DEWAR; Type 0: Not a Combination Product	11/01/2011	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	11/01/2011	

Labeler - - INDUSTRIAL WELDING SUPPLY CO. OF HARVEY, INC. (050958362)

Establishment

Name	Address	ID/FEI	Business Operations
INDUSTRIAL WELDING SUPPLY CO. OF HARVEY, INC.		050958362	manufacture(42241-001)

Revised: 10/2024

- INDUSTRIAL WELDING SUPPLY CO. OF HARVEY, INC.