

**OXYGEN- oxygen gas**  
**Intermountain Home Care**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

-----  
**Oxygen**

**OXYGEN COMPRESSED U.S.P. UN 1072**

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

WARNING: HIGH PRESSURE OXIDIZING GAS

VIGOROUSLY ACCELERATES COMBUSTION

Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.

Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.

DO NOT REMOVE THIS PRODUCT LABEL.

Use a back flow preventive device in the piping.

Use only in accordance with product instructions and material safety data sheet.

WARNING:

HIGH PRESSURE GAS CYLINDER

Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been refinished and/or exposed to elevated temperatures must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve

manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.

<p>Produced by air liquefaction</p> <div style="border: 1px solid black; padding: 5px; display: inline-block;"> <p><b>OXYGEN COMPRESSED U.S.P. UN 1072</b></p> </div>  <p><b>WARNING:</b> For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: <b>Rx ONLY</b>. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.</p> <p><b>WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION</b></p> <ul style="list-style-type: none"> <li>▶ Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.</li> <li>▶ Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.</li> <li>▶ Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food Drug, and Cosmetic Act.</li> <li>▶ Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.</li> <li>▶ <b>DO NOT REMOVE THIS PRODUCT LABEL</b></li> <li>▶ Use a back flow preventive device in the piping.</li> <li>▶ Use only in accordance with product instructions and material safety data sheet.</li> </ul>	<p>Distributed by:</p>  <p><b>Intermountain Homecare</b> <i>Healing for life</i></p> <p><b>(800) 527-1118</b></p>	<p><b>WARNING:</b> <b>HIGH PRESSURE GAS CYLINDER</b></p> <p>Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been refinished and/or exposed to elevated temperature must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.</p> <div style="border: 1px solid black; padding: 5px; text-align: center;"> <p><b>B-CYLINDER</b>  <b>CONTENTS: 170/6 LITERS/CU.FT</b>  <b>PRESSURE: 2216 PSIG AT 70° F</b></p> </div> <p style="text-align: right; font-size: small;">B 9/13</p>
--	--	---

<p>Produced by air liquefaction</p> <div style="border: 1px solid black; padding: 5px; display: inline-block;"> <p><b>OXYGEN COMPRESSED U.S.P. UN 1072</b></p> </div>  <p><b>WARNING:</b> For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: <b>Rx ONLY</b>. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.</p> <p><b>WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION</b></p> <ul style="list-style-type: none"> <li>▶ Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.</li> <li>▶ Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.</li> <li>▶ Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food Drug, and Cosmetic Act.</li> <li>▶ Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.</li> <li>▶ <b>DO NOT REMOVE THIS PRODUCT LABEL</b></li> <li>▶ Use a back flow preventive device in the piping.</li> <li>▶ Use only in accordance with product instructions and material safety data sheet.</li> </ul>	<p>Distributed by:</p>  <p><b>Intermountain Homecare</b> <i>Healing for life</i></p> <p><b>(800) 527-1118</b></p>	<p><b>WARNING:</b> <b>HIGH PRESSURE GAS CYLINDER</b></p> <p>Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been refinished and/or exposed to elevated temperature must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.</p> <div style="border: 1px solid black; padding: 5px; text-align: center;"> <p><b>C-CYLINDER</b>  <b>CONTENTS: 255/9 LITERS/CU.FT</b>  <b>PRESSURE: 2015 PSIG AT 70° F</b></p> </div> <p style="text-align: right; font-size: small;">C 9/13</p>
--	--	---

Produced by air liquefaction

**OXYGEN  
COMPRESSED  
U.S.P. UN 1072**



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: **Rx ONLY.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION**

- ▶ Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- ▶ Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- ▶ Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food Drug, and Cosmetic Act.
- ▶ Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.
- ▶ **DO NOT REMOVE THIS PRODUCT LABEL.**
- ▶ Use a back flow preventive device in the piping.
- ▶ Use only in accordance with product instructions and material safety data sheet.

Distributed by:

**Intermountain  
Homecare**  
*Healing for life*

**(800) 527-1118**

**WARNING:**

**HIGH PRESSURE GAS CYLINDER**

Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been refinished and/or exposed to elevated temperature must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.

**WARNING: THESE ARE APPROXIMATE TIMES ONLY**

D-CYLINDER LITER FLOW	CONTENTS LITER FLOW FULL TANK 2000 PSI	CONTENTS:	425/15	LITERS/CU.FT.
1/10	50 HOURS			
1/8	40 HOURS			
1/4	23 HOURS			
1/2	11 HOURS			
3/4	8 HOURS			
1	5 HOURS			
		PRESSURE:	2015	PSIG AT 70°F

D 9/13

Produced by air liquefaction

**OXYGEN  
COMPRESSED  
U.S.P. UN 1072**



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: **Rx ONLY.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION**

- ▶ Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- ▶ Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- ▶ Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food Drug, and Cosmetic Act.
- ▶ Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.
- ▶ **DO NOT REMOVE THIS PRODUCT LABEL.**
- ▶ Use a back flow preventive device in the piping.
- ▶ Use only in accordance with product instructions and material safety data sheet.

Distributed by:

**Intermountain  
Homecare**  
*Healing for life*

**(800) 527-1118**

**WARNING:**

**HIGH PRESSURE GAS CYLINDER**

Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been refinished and/or exposed to elevated temperature must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.

**WARNING: THESE ARE APPROXIMATE TIMES ONLY**

E-CYLINDER LITER FLOW	CONTENTS LITER FLOW FULL TANK 2000 PSI	E-CYLINDER LITER FLOW	CONTENTS LITER FLOW FULL TANK 2000 PSI	CONTENTS:	680/24	LITERS/CU.FT.
1/10	100 HOURS	3	3.4 HOURS			
1/8	83 HOURS	4	2.5 HOURS			
1/4	41 HOURS	5	2.0 HOURS			
1/2	20 HOURS	6	1.7 HOURS			
3/4	13 HOURS					
1	10 HOURS					
2	5 HOURS					
				PRESSURE:	2015	PSIG AT 70°F

E 9/13

Produced by air liquefaction

**OXYGEN  
COMPRESSED  
U.S.P. UN 1072**



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: **Rx ONLY.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**WARNING: HIGH PRESSURE OXIDIZING GAS  
VIGOROUSLY ACCELERATES COMBUSTION**

- ▶ Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- ▶ Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- ▶ Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food Drug, and Cosmetic Act.
- ▶ Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.
- ▶ **DO NOT REMOVE THIS PRODUCT LABEL.**
- ▶ Use a back flow preventive device in the piping.
- ▶ Use only in accordance with product instructions and material safety data sheet.

Distributed by:



**Intermountain  
Homecare**  
*Healing for life*

**(800) 527-1118**

**WARNING:**  
**HIGH PRESSURE GAS CYLINDER**

Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. **DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE.** Keep out of the reach of children. Cylinders that have been refinished and/or exposed to elevated temperature must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. **DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING.** Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.

**WARNING: THESE ARE APPROXIMATE TIMES ONLY**

M-CYLINDER LITER FLOW	CONTENTS LITER FLOW FULL TANK 2000 PSI
1/10	24.0 DAYS
1/8	19.0 DAYS
1/4	9.5 DAYS
1/2	4.5 DAYS
1	2.4 DAYS
2	28 HOURS
3	19 HOURS

CONTENTS: 3455/122 LITERS/CU.FT  
PRESSURE: 2216 PSIG AT 70° F

M 9/13

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:62179-1234
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	1 L in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:62179-1234-1	255 L in 1 CYLINDER; Type 0: Not a Combination Product	01/13/2022	
2	NDC:62179-1234-2	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/13/2022	
3	NDC:62179-1234-3	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/13/2022	
4	NDC:62179-1234-4	3455 L in 1 CYLINDER; Type 0: Not a Combination Product	01/13/2022	

### Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical		07/18/2014	

gas		07/10/2014	
-----	--	------------	--

**Labeler** - Intermountain Home Care (079549773)

**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Intermountain Home Care		079549773	manufacture(62179-1234)

Revised: 12/2025

Intermountain Home Care