

OXYGEN- oxygen gas
Sparrow Medical Supply L.L.C.

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Labels

Oxygen Label 1

Produced by Air Liquide

OXYGEN COMPRESSED U.S.P. UN 1072



Distributed by:

SPARROW
 REGIONAL
 MEDICAL SUPPLY

WARNING:
HIGH PRESSURE GAS CYLINDER
 Improper filling or abuse of this cylinder, or failure to follow the warning may cause death or injury to those of the following: NOT A USER OR MOBILE CYLINDER OR RELIEF COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been overfilled and/or exposed to excessive temperatures, or that are hydrostatically tested using filling. Do not use portable liquid oxygen. Aluminum cylinders subject to action of fire or heated in temperatures in excess of 300°F may be filled with both oxygen and acetylene. Safety and safety relief devices must be maintained and repaired by trained personnel. Do not charge or charge safety devices. Replace pressure relief devices only with original assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GAS. CAUTION: WASH WITH CLEANING CYCLIDEX valves and assemblies must be specially cleaned to oxygen. Verify cylinder content and pressure monthly or more frequently if stored. Store and use with adequate ventilation.

WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION

- Use only with pressure reducing equipment in accordance with the design of oxygen service and rated for oxygen service.
- Open valve slowly. Check valve after each use and when closed. Keep cylinder, cylinder valve, and equipment filled to neck, free of oil and grease to avoid cylinder failure.
- Federal law requires that this cylinder be refilled with oxygen U.S.P. only by establishments registered as a filling manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.
- Follow all recommendations by Compressed Gas Association for safe use of oxygen cylinders in temperatures in excess of 125°F.
- DO NOT REMOVE THIS PRODUCT LABEL.

Use only in accordance with printed instructions and machine safety data sheet.

915 East Michigan Avenue
 Lansing, MI 48912

(877) 205-3500
 (517) 364-2115

Cylinder contents at 70°F	
Type	
○ A	- 113 liters at 2216 PSI
○ B	- 164 liters at 2216 PSI
○ C	- 248 liters at 2015 PSI
○ D	- 414 liters at 2015 PSI
○ E	- 682 liters at 2015 PSI
○ Q	- 1723 liters at 2216 PSI

Oxygen label 2

CYLINDER FILLED BY

Oxygen U.S.P. Refrigerated Liquid

UN1073
WARNING!
 Extremely cold liquid and gas under pressure. Vigorously accelerates combustion.



PRODUCED BY AIR LIQUEFACTION

SPARROW
 REGIONAL
 MEDICAL SUPPLY

915 East Michigan Avenue
 Lansing, MI 48912

(877) 205-3500
 (517) 364-2115

Warning!
 For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. Can cause extreme frost bite.

Keep Out of Reach of Children.
 Contents under pressure and can vigorously accelerate combustion. Keep free from oil and grease. Do not use or store near heat or open flame and use only with equipment conditioned for oxygen service. Open valve slowly. Close valve when not in use and when empty. Store and use with adequate ventilation to prevent oxygen accumulation.

LQTY. _____ EXP. _____ LITERS _____

Caution: Federal law prohibits dispensing without prescription. For other medical applications, use only as directed by a licensed practitioner. Unintended use of high concentrations of oxygen for more than 6 hours, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen.

Federal law requires that this cylinder be refilled with Oxygen, U.S.P. only by establishments registered as a drug producer in accordance with the Federal Food, Drug and Cosmetic Act.

DO NOT REMOVE THIS LABEL

Oxygen Label 3

Oxygen, Refrigerated Liquid U.S.P.

WARNING!



DO NOT CHANGE OR FORCE FIT CONNECTIONS. EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquification.

Contents: _____ LITERS

CYLINDER FILLED BY

SPARROW

REGIONAL
MEDICAL SUPPLY

915 East Michigan Avenue
Lansing, MI 48912

(877) 205-3500
(517) 364-2115

WARNING!

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drip. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Container temperature should not exceed 62 C (125F). Close valve after each use and when empty. Use a leak flow preventative device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).
FIRST AID:
IN CASE OF FROSTBITE, obtain medical treatment immediately.

DO NOT REMOVE THIS LABEL

Oxygen Label 4

Produced by air liquification

**OXYGEN
COMPRESSED
U.S.P. UN 1072**



Distributed by:



915 East Michigan Avenue
Lansing, MI 48912

(877) 205-3500
(517) 364-2115

WARNING:

HIGH PRESSURE GAS CYLINDER
Improper filling or abuse of this cylinder, or failure to heed this warning may cause serious injury or loss of life. DO NOT ALTER OR MODIFY CYLINDER OR RELATED COMPONENTS. DO NOT OVER PRESSURIZE. Keep out of the reach of children. Cylinders that have been refilled and/or exposed to elevated temperatures must be hydrostatically tested before filling. Do not use caustic paint strippers. Aluminum cylinders subject to action of fire or heated to temperatures in excess of 350°F must be withdrawn from service and condemned. Valves and safety relief devices must be removed and replaced by trained personnel. Do not alter or change safety discs. Replace pressure relief devices only with complete assemblies supplied by the valve manufacturer. DO NOT FILL WITH OXIDIZING GASES WITHOUT PROPER CLEANING. Cylinders, valves, and assemblies must be specially cleaned for oxygen. Verify cylinder content and pressure monthly, or more frequently if required. Store and use with adequate ventilation.

Cylinder contents at 70°F

Type	Contents
O A	- 113 liters at 2216 PSI
O B	- 164 liters at 2216 PSI
O C	- 248 liters at 2015 PSI
O D	- 414 liters at 2015 PSI
O E	- 682 liters at 2015 PSI
O Q	- 1723 liters at 2216 PSI

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

WARNING: HIGH PRESSURE OXIDIZING GAS VIGOROUSLY ACCELERATES COMBUSTION

- > Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- > Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- > Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.
- > Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.
- > **DO NOT REMOVE THIS PRODUCT LABEL.**

Date code: 1102

Label: 005-1702

Oxygen Label 5

Oxygen, Refrigerated Liquid U.S.P.

WARNING!



DO NOT CHANGE OR FORCE FIT CONNECTIONS, EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Contents: _____ LITERS

CYLINDER FILLED BY



915 East Michigan Avenue
Lansing, MI 48912

(877) 205-3500
(517) 364-2115

WARNING!

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drip. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Container temperature should not exceed 52 C (125F). Close valve after each use and when empty. Use a back flow preventative device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS)
FIRST AID:
IN CASE OF FROSTBITE, obtain medical treatment immediately.

DO NOT REMOVE THIS LABEL

Oxygen Label 6

Produced by air liquefaction

**OXYGEN
COMPRESSED
U.S.P. UN 1072**

DANGER

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**WARNING: HIGH PRESSURE OXIDIZING GAS
VIGOROUSLY ACCELERATES COMBUSTION**

- Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.
- Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.
- DO NOT REMOVE THIS PRODUCT LABEL.

Use only in accordance with product instructions and material safety data sheet.
Date code: 1102 Label: C035-170(2)

Distributed by:

915 East Michigan Avenue
Lansing, MI 48912

(877) 205-3500
(517) 364-2115

Cylinder contents at 70°F

Type	Capacity
O A	113 liters at 2216 PSI
O B	164 liters at 2216 PSI
O C	248 liters at 2015 PSI
O D	414 liters at 2015 PSI
O E	682 liters at 2015 PSI
O Q	1723 liters at 2216 PSI



Oxygen Label 7



Oxygen Label 8

**Oxygen, Refrigerated
Liquid U.S.P.**


WARNING! DO NOT CHANGE OR FORCE FIT CONNECTIONS, EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

WARNING:
For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Contents: _____ LITERS

CYLINDER FILLED BY



915 East Michigan Avenue
Lansing, MI 48912

(877) 205-3500
(517) 364-2115

DANGER

WARNING!

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal wear face shield and gloves. Do not drip. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Container temperature should not exceed 52 C (125F). Close valve after each use and when empty. Use a back flow preventative device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS)

FIRST AID:
IN CASE OF FROSTBITE, obtain medical treatment immediately.

DO NOT REMOVE THIS LABEL

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:54595-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:54595-001-50	248 L in 1 CYLINDER; Type 0: Not a Combination Product	12/05/1994	
2	NDC:54595-001-40	164 L in 1 CYLINDER; Type 0: Not a Combination Product	12/05/1994	
3	NDC:54595-001-60	414 L in 1 CYLINDER; Type 0: Not a Combination Product	12/05/1994	
4	NDC:54595-001-70	682 L in 1 CYLINDER; Type 0: Not a Combination Product	12/05/1994	
5	NDC:54595-001-90	184 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
6	NDC:54595-001-30	113 L in 1 CYLINDER; Type 0: Not a Combination Product	12/05/1994	
7	NDC:54595-001-80	1723 L in 1 CYLINDER; Type 0: Not a Combination Product	12/05/1994	
8	NDC:54595-001-91	7749 L in 1 CYLINDER; Type 0: Not a Combination Product	12/05/1994	
9	NDC:54595-001-10	46 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
10	NDC:54595-001-20	30 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	

11	NDC:54595-001-21	46 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
12	NDC:54595-001-22	36 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
13	NDC:54595-001-23	10 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
14	NDC:54595-001-24	720 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
15	NDC:54595-001-25	225 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
16	NDC:54595-001-26	451 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	
17	NDC:54595-001-27	277 L in 1 DEWAR; Type 0: Not a Combination Product	12/05/1994	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		07/01/1994	

Labeler - Sparrow Medical Supply L.L.C. (837040336)

Registrant - Sparrow Medical Supply L.L.C. (837040336)

Establishment

Name	Address	ID/FEI	Business Operations
Sparrow Medical Supply L.L.C.		837040336	manufacture(54595-001)

Revised: 10/2020

Sparrow Medical Supply L.L.C.