

OXYGEN - oxygen gas
Four Corners Welding

Oxygen Labels

OXYGEN
REFRIGERATED LIQUID USP
UN1073

OXYGEN 2
ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING

For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only.
Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52 degrees C (125 degrees F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

SECURE ALL CYLINDERS WHILE IN STORAGE AND IN USE.

DO NOT REMOVE THIS PRODUCT LABEL.

FOUR CORNERS

WELDING AND GAS SUPPLY

606 EAST HIGHWAY 66 GALLUP, NM 87301

505-722-3845

OXYGEN, REFRIGERATED LIQUID USP UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION!

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.



For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Container temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

• **IN CASE OF FROSTBITE, obtain medical treatment immediately.**

CAS: 7782-44-7



SECURE ALL CYLINDERS WHILE IN STORAGE AND IN USE.

DO NOT REMOVE THIS PRODUCT LABEL.

FOUR CORNERS
WELDING & GAS SUPPLY
606 EAST HIGHWAY 66 • GALLUP, NM 87301
505-722-3845

LABS-501020-00-00-1001-0000 0001 0000

OXYGEN,
COMPRESSED
USP
UN1072

OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS NUMBER: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

FOUR CORNERS WELDING AND GAS SUPPLY

606 EAST HWY 66

GALLUP, NM 87301

CONTENTS:

LTRS:

CO.FT:

**OXYGEN,
COMPRESSED
USP**

UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, rapidly discontinued use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquide/air. **WARNINGS:** HIGH PRESSURE OXYGEN GAS VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Use only for Oxygen service and rated for cylinder pressure. Use a back flow prevention device in low piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (123°F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7. **DO NOT REMOVE THIS PRODUCT LABEL.**

4 CORNERS WELDING & GAS SUPPLY
606 EAST HWY 66
GALLUP, NM 87301

CONTENTS: LBS.
CU FT.

OXYGEN

oxygen gas

Product Information

| | | | |
|--------------------------------|--------------------------|---------------------------|---------------|
| Product Type | PRESCRIPTION ANIMAL DRUG | Item Code (Source) | NDC:13826-011 |
| Route of Administration | RESPIRATORY (INHALATION) | | |

Active Ingredient/Active Moiety

| Ingredient Name | Basis of Strength | Strength |
|--|-------------------|---------------|
| Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065) | Oxygen | 990 mL in 1 L |

Packaging

| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
|----|------------------|----------------------|----------------------|--------------------|
| 1 | NDC:13826-011-01 | 9344 L in 1 CYLINDER | | |
| 2 | NDC:13826-011-02 | 8495 L in 1 CYLINDER | | |
| 3 | NDC:13826-011-03 | 6230 L in 1 CYLINDER | | |
| 4 | NDC:13826-011-04 | 4247 L in 1 CYLINDER | | |
| 5 | NDC:13826-011-05 | 3454 L in 1 CYLINDER | | |
| 6 | NDC:13826-011-06 | 2265 L in 1 CYLINDER | | |
| 7 | NDC:13826-011-07 | 1132 L in 1 CYLINDER | | |
| 8 | NDC:13826-011-08 | 566 L in 1 CYLINDER | | |
| 9 | NDC:13826-011-09 | 639 L in 1 CYLINDER | | |
| 10 | NDC:13826-011-10 | 424 L in 1 CYLINDER | | |
| 11 | NDC:13826-011-11 | 254 L in 1 CYLINDER | | |
| 12 | NDC:13826-011-12 | 169 L in 1 CYLINDER | | |
| 13 | NDC:13826-011-13 | 113 L in 1 CYLINDER | | |
| 14 | NDC:13826-011-14 | 127425 L in 1 DEWAR | | |
| 15 | NDC:13826-011-15 | 155742 L in 1 DEWAR | | |
| 16 | NDC:13826-011-16 | 325926 L in 1 DEWAR | | |
| 17 | NDC:13826-011-17 | 387855 L in 1 DEWAR | | |

Marketing Information

| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
|--------------------|--|----------------------|--------------------|
| NADA | NADA141396 | 01/01/1985 | |

Labeler - Four Corners Welding (097968531)

Establishment

| Name | Address | ID/FEI | Business Operations |
|----------------------|---------|-----------|---------------------|
| Four Corners Welding | | 619216591 | manufacture |

Establishment

| Name | Address | ID/FEI | Business Operations |
|----------------------|---------|-----------|---------------------|
| Four Corners Welding | | 807672449 | manufacture |

Establishment

| Name | Address | ID/FEI | Business Operations |
|----------------------|---------|-----------|---------------------|
| Four Corners Welding | | 097968531 | manufacture |

Revised: 6/2014

Four Corners Welding