

OXYGEN- oxygen gas
A & E Mill & Welding Supply Company

oxygen

OXYGEN, COMPRESSED USP
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

A&E MILL & WELDING SUPPLY COMPANY
920 INDUSTRIAL BLVD
LONE STAR TX 75668 903-656-3485
CONTENTS: LTRS CU.FT.
NO SMOKING
NO VAPING

OXYGEN,
COMPRESSED
USP
UN1072
PRODUCED BY AIR LIQUEFACTION



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS: LTRS CU. FT.

NO SMOKING
NO VAPING



A&E MILL & WELDING SUPPLY COMPANY
920 INDUSTRIAL BLVD
LONE STAR TX 75668 • 903-656-3485

OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:70273-011
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:70273-011-09	7060 L in 1 CYLINDER		
2	NDC:70273-011-10	3160 L in 1 CYLINDER		
3	NDC:70273-011-11	690 L in 1 CYLINDER		
4	NDC:70273-011-12	420 L in 1 CYLINDER		
5	NDC:70273-011-13	246 L in 1 CYLINDER		
6	NDC:70273-011-14	198 L in 1 CYLINDER		
7	NDC:70273-011-15	164 L in 1 CYLINDER		
8	NDC:70273-011-16	113 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141365	06/30/1992	

Labeler - A & E Mill & Welding Supply Company (004998720)

Establishment

Name	Address	ID/FEI	Business Operations
A & E Mill & Welding Supply Company		004998720	manufacture

Revised: 11/2025

A & E Mill & Welding Supply Company