

OXYGEN- oxygen gas
Mississippi Welders Supply Company, Inc.

Oxygen

OXYGEN, COMPRESSED USP

UN1072

OXYGEN 2

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patient's who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL


MISSISSIPPI WELDERS SUPPLY CO., INC.

5150 W 6TH STREET

WINONA, MN 55987

507-454-5231

CONTENTS LTRS CU.FT.



Oxygen, Refrigerated

Liquid

UN 1073

Oxygen, USP

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

DO NOT CHANGE OR FORCE FIT CONNECTIONS

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE OR IGNITE ON IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX Only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

DO NOT REMOVE THIS PRODUCT LABEL

Mississippi Welders Supply Company
Winona, MN 55987

507-454-5231 Contents: _____

(Rev.18 September 2018)

Oxygen, Refrigerated
Liquid
UN 1073



Oxygen, USP

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS**

DANGER: MAY CAUSE OR INTENSIFY FIRE. OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE OR IGNITE ON IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **RX Only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

DO NOT REMOVE THIS PRODUCT LABEL

Mississippi Welders Supply Company

Winona, MN 55987
507-454-5231
(Rev. 18 September 2018)

Contents: _____

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:51996-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:51996-001-01	396 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
2	NDC:51996-001-02	651 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
3	NDC:51996-001-03	3582 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
4	NDC:51996-001-04	6510 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
5	NDC:51996-001-05	8516 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
6	NDC:51996-001-06	141 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	

7	NDC:51996-001-07	234 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
8	NDC:51996-001-08	387 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
9	NDC:51996-001-09	643 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
10	NDC:51996-001-10	1699 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
11	NDC:51996-001-11	2540 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
12	NDC:51996-001-12	4361 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
13	NDC:51996-001-13	7100 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
14	NDC:51996-001-14	9401 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
15	NDC:51996-001-15	127237 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
16	NDC:51996-001-16	164 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205840	01/01/1976	

Labeler - Mississippi Welders Supply Company, Inc. (078691540)

Establishment

Name	Address	ID/FEI	Business Operations
Mississippi Welders Supply Company, Inc.		078691540	manufacture(51996-001)

Establishment

Name	Address	ID/FEI	Business Operations
Mississippi Welders Supply Company, Inc.		147577555	manufacture(51996-001)

Revised: 11/2024

Mississippi Welders Supply Company, Inc.