

**OXYGEN- oxygen gas**  
**Industrial Welding & Tool Supply, Ltd.**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2. WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL. GAS AND SUPPLY. 8595 W 81ST SOUTH. Tulsa, OK 74131 (918) 224-6455. CONTENTS: LTRS. CU. FT.



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP OXYGEN 2 UN1073 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. CONTENTS: LTRS: CU FT: WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or

clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS). FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL. GAS AND SUPPLY 8595 W 81ST South. Tulsa, OK 74131 (918)

**REFRIGERATED LIQUID**

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**



**UN1073**

**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: \_\_\_\_\_

LTRS:

CU FT:

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R<sub>x</sub> only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

**Produced by Air Liquefaction.**

**WARNING:** EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.  
VIGOROUSLY ACCELERATES COMBUSTION.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT  
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52°C (125°F)  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the **Material Safety Data Sheet (MSDS).**

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**
 8595 W. 81<sup>ST</sup> South  
 Tulsa, OK 74131  
 (918)224-6455

 47136  
 (R 10/05)

224-6455

**OXYGEN**

oxygen gas

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:58404-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:58404-001-01	198 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
2	NDC:58404-001-02	424 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
3	NDC:58404-001-03	707 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
4	NDC:58404-001-04	3228 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
5	NDC:58404-001-05	3539 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
6	NDC:58404-001-06	6456 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
7	NDC:58404-001-07	7107 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
8	NDC:58404-001-08	7249 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
9	NDC:58404-001-09	7957 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
10	NDC:58404-001-10	8693 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
11	NDC:58404-001-11	9542 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
12	NDC:58404-001-12	180 L in 1 DEWAR; Type 0: Not a Combination Product	05/01/2013	
13	NDC:58404-	200 L in 1 DEWAR; Type 0: Not a Combination	05/01/2013	

001-13	Product	05/01/2013	
<b>Marketing Information</b>			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205865	05/01/2013	

**Labeler** - Industrial Welding & Tool Supply, Ltd. (078785627)

<b>Establishment</b>			
Name	Address	ID/FEI	Business Operations
INDUSTRIAL WELDING & TOOL SUPPLY, LTD.		078785627	manufacture(58404-001)

Revised: 10/2024

Industrial Welding & Tool Supply, Ltd.