

OXYGEN- oxygen gas
California Tool and Welding Supply, LLC

Oxygen

OXYGEN, COMPRESSED USP

UN1072

PRODUCED AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS: LTRS:

CU FT:

CALIFORNIA TOOL & WELDING SUPPLY

201 NORTH MAIN STREET RIVERSIDE, CA 92501

(951) 686-7822

NO SMOKING

NO VAPING

**OXYGEN,
COMPRESSED
USP**
UN1072
PRODUCED BY AIR LIQUEFACTION



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.



CALIFORNIA TOOL & WELDING SUPPLY
201 NORTH MAIN STREET • RIVERSIDE, CA 92501
(951) 686-7822

CONTENTS: LTRS NO SMOKING
cu. ft. NO VAPING



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx required.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Always keep container in upright position. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

NO SMOKING

NO VAPING

CALIFORNIA TOOL & WELDING SUPPLY

201 NORTH MAIN STREET RIVERSIDE, CA 92501

(951) 686-7822

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073**



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, R **required**.
Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.
Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH OXIDIZING REFRIGERATED LIQUIDS MAY EXPLODE ON IGNITION OR IMPACT.
Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves and either face shield or eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Always keep container in upright position. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Read and follow the Safety Data Sheet (SDS) before use.



FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

**NO SMOKING
NO VAPING**



CALIFORNIA TOOL & WELDING SUPPLY
201 NORTH MAIN STREET • RIVERSIDE, CA 92501
(951) 686-7822 41533
(01/25)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:14208-532
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety		
Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:14208-532-01	113 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
2	NDC:14208-532-02	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
3	NDC:14208-532-05	210 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
4	NDC:14208-532-07	250 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
5	NDC:14208-532-09	651 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
6	NDC:14208-532-11	1728 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
7	NDC:14208-532-12	102 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
8	NDC:14208-532-13	150 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
9	NDC:14208-532-14	255 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
10	NDC:14208-532-03	400 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
11	NDC:14208-532-04	660 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
12	NDC:14208-532-06	3450 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
13	NDC:14208-532-08	6900 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
14	NDC:14208-532-10	8500 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1976	
15	NDC:14208-532-15	26660 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
16	NDC:14208-532-16	86055 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
17	NDC:14208-532-17	137688 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
18	NDC:14208-532-18	154800 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
19	NDC:14208-532-19	145340 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
20	NDC:14208-532-20	154800 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
21	NDC:14208-532-21	154800 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
22	NDC:14208-532-22	172000 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
23	NDC:14208-532-23	184164 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
24	NDC:14208-532-24	197800 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1976	
25	NDC:14208-	227900 L in 1 DEWAR; Type 0: Not a Combination	01/01/1976	

532-25	Product	01/01/1976	
Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1976	

Labeler - California Tool and Welding Supply, LLC (070941877)

Registrant - California Tool and Welding Supply, LLC (070941877)

Establishment			
Name	Address	ID/FEI	Business Operations
California Tool and Welding Supply, LLC		070941877	manufacture(14208-532)

Revised: 10/2025

California Tool and Welding Supply, LLC