

AIR- air gas
PURITY CYLINDER GASES INC

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

AIR

AIR, COMPRESSED

UN1002 (MEDICAL AIR, USP)

NON-FLAMMABLE GAS 2

37318 (R 12/05)

WARNING: For breathing support when used by properly trained personnel. For medical applications, **Rx only**. Administration of medical air may be hazardous or contraindicated. For medical use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of medical air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration and with the hazards, contraindications and side effects, and the precautions to be taken. **CAUTION: HIGH PRESSURE GAS MAY ACCELERATE COMBUSTION.** Keep oil and grease away. Use equipment rated for cylinder pressure. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the **Material Safety Data Sheet (MSDS)**. CAS: 132259-10-0

DO NOT REMOVE THIS PRODUCT LABEL

PURITY CYLINDER GASES, INC.
 GRAND RAPIDS, MI

CONTENTS: LTRS. CU. FT.

AIR

CONTENTS: LTRS. CU. FT.

WARNING: For breathing support when used by properly trained personnel. For medical applications, **Rx only**. Administration of medical air may be hazardous or contraindicated. For medical use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of medical air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration and with the hazards, contraindications and side effects, and the precautions to be taken. **CAUTION: HIGH PRESSURE GAS MAY ACCELERATE COMBUSTION.** Keep oil and grease away. Use equipment rated for cylinder pressure. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the **Material Safety Data Sheet (MSDS)**. CAS: 132259-10-0

DO NOT REMOVE THIS PRODUCT LABEL

PURITY CYLINDER GASES, INC.
 GRAND RAPIDS, MI

| # | Item Code | Package Description | Marketing Start Date | Marketing End Date |
|---|------------------|---|----------------------|--------------------|
| 1 | NDC:10927-104-03 | 682 L in 1 CYLINDER; Type 0: Not a Combination Product | 10/20/1938 | |
| 2 | NDC:10927-104-04 | 6654 L in 1 CYLINDER; Type 0: Not a Combination Product | 10/20/1938 | |

| Marketing Information | | | |
|------------------------|--|----------------------|--------------------|
| Marketing Category | Application Number or Monograph Citation | Marketing Start Date | Marketing End Date |
| unapproved medical gas | | 10/20/1938 | |

Labeler - PURITY CYLINDER GASES INC (065878860)

Establishment

| Name | Address | ID/FEI | Business Operations |
|---------------------------|---------|-----------|------------------------|
| PURITY CYLINDER GASES INC | | 120042374 | manufacture(10927-104) |

Revised: 12/2015

PURITY CYLINDER GASES INC