

OXYGEN - oxygen gas
Rochester Welding Supply Corp.

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

OXYGEN COMPRESSED LABEL

OXYGEN COMPRESSED USP - OXYGEN-2

PRESSURE: _____ PSIG AT 70 F SIZE: _____ CONTENTS _____ LITERS
RETURN WITH 25 PSIG. UN 1072

PRODUCED BY AIR LIQUEFACTION TO BE REFILLED BY RWS AUTHORIZED FACILITY
ONLY CAS 7782-44-7 RWSLB2 REV 01/09

Pressure: _____ PSIG at 70°F
Size: _____
Contents: _____ liters
Return with 25 PSIG

**OXYGEN,
COMPRESSED
USP
UN 1072**

**OXYGEN
2**

**ROCHESTER
WELDING SUPPLY Corp.**
510 STATE STREET, ROCHESTER, NY 14608

WARNING: High Pressure Oxidizing Gas, Vigorously Accelerates Combustion. Keep all oil, grease, and hydrocarbons away. Use only with equipment designed and cleaned for oxygen service, and rated for cylinder pressure. Open valve slowly and close after each use. Always secure cylinder. Store and use with adequate ventilation. Use a back flow prevention device in the piping. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with RWS MSDS-OXY.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY.

WARNING: Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**PRODUCED BY AIR LIQUEFACTION
DO NOT REMOVE THIS PRODUCT LABEL
TO BE REFILLED BY RWS AUTHORIZED FACILITY ONLY.**

RWSLB2 Rev 01/09 CAS 7782-44-7

OXYGEN COMPRESSED LABEL

OXYGEN COMPRESSED USP - OXYGEN-2

PRESSURE: _____ PSIG AT 70 F SIZE: _____ CONTENTS _____ LITERS
RETURN WITH 25 PSIG. UN 1072

PRODUCED BY AIR LIQUEFACTION TO BE REFILLED BY RWS AUTHORIZED FACILITY
ONLY CAS 7782-44-7 RWSLB3 REV 01/09 MADE IN THE USA



REFRIGERATED LIQUID LABEL

OXYGEN REFRIGERATED LIQUID U.S.P. UN 1073 OXYGEN-2

GROSS WT: _____ LBS. OZ. NET WT. _____ LBS. OZ. SIZE _____
CONTENTS _____ LITERS

OXYGEN PRODUCED BY AIR LIQUEFACTION ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

FOR LIQUID WITHDRAWAL WEAR FACE SHIELD AND GLOVES. DO NOT GET LIQUID IN EYES, ON SKIN OR CLOTHING. DO NOT DROP. USE HAND TRUCK SPECIFICALLY DESIGNED FOR LIQUID CYLINDER MOVEMENT. AVOID SPILLS. DO NOT WALK OR ROLL EQUIPMENT OVER SPILLS. USE IN ACCORDANCE WITH RWS MSDS-G046

IN CASE OF FROSTBITE OBTAIN MEDICAL TREATMENT IMMEDIATELY. CAS 7782-44-7
RWSLB5 REV 01/09 OXYGEN PRODUCED BY AIR LIQUEFACTION



ROCHESTER
WELDING SUPPLY Corp.

510 STATE STREET, ROCHESTER, NY 14608

OXYGEN, *

REFRIGERATED LIQUID

U.S.P. UN 1073



Gross Wt.:	lbs.	oz.	
Net Wt.:	lbs.	oz.	
Size:	Contents	Liters	

*Oxygen produced by air liquefaction

WARNING: ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away. Use only with equipment cleaned for oxygen service. Use only with equipment designated for and compatible with oxygen and rated for cylinder pressure. Container temperature should not exceed 52 degrees C (125 degrees F). Use a back flow preventive device in the piping. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck specifically designed for liquid cylinder movement. Avoid spills. Do not walk or roll equipment over spills. Close valve after each use and when empty. Use in accordance with RWS MSDS-G046.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY.

WARNING: Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep out of the reach of children.



RWSLB5 Rev 01/09

IN CASE OF FROSTBITE, obtain medical treatment immediately.

TO BE REFILLED BY RWS AUTHORIZED FACILITY ONLY. CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN CERTIFICATE OF ANALYSIS

LOT NUMBER _____ SERIAL NUMBER _____ AMOUNT _____ INS. LBS GALS
LITERS CU FT

USP TESTS

TEST ID ODOR ASSAY

LIMITS OK NONE GREATER THAN OR EQUAL TO 99.2%

RESULTS _____

FOR CUSTOMER USE TO DOCUMENT TESTS PERFORMED ON THIS VESSEL

METHOD OF ANALYSIS IS THE PARAMAGNETIC OXYGEN ANALYZER

MANUFACTURER _____ MODEL _____ CUSTOMER WITNESSED TESTS YES _____

MO _____ SUPPLIERS SIGNATURE _____ DATE _____ CUSTOMER'S

SIGNATURE _____ DATE _____

LIQUID OXYGEN DELIVERY TAG THIS VESSEL CONTAINS OXYGEN U.S.P. (SEE REVERSE SIDE FOR TEST RESULTS) OXYGEN PRODUCED BY THE AIR LIQUEFACTION PROCESS - MEDICAL GASES


MANUFACTURED BY ROCHESTER WELDING SUPPLY CORP 510 STATE STREET ROCHESTER, NY 14608 585-325-4730

LOT NUMBER _____ SERIAL NUMBER _____
AMOUNT _____ INS., LBS., GALS., LITERS, CU. FT.

USP TESTS			
TEST	ID	ODOR	ASSAY
LIMITS	OK	NONE	≥99.2%
RESULT			

FOR CUSTOMER USE TO DOCUMENT TESTS PERFORMED ON THIS VESSEL	

METHOD OF ANALYSIS FOR ASSAY IS THE PARAMAGNETIC OXYGEN ANALYZER
MANUFACTURER _____ MODEL _____
CUSTOMER WITNESSED TESTS: YES NO
SUPPLIER'S SIGNATURE _____ DATE _____
CUSTOMER'S SIGNATURE _____ DATE _____

 **Medical Gases**
LIQUID OXYGEN DELIVERY TAG

MANUFACTURED BY:

Rochester Welding Supply Corp. 510 State Street Rochester, NY 14608 585-325-4730

THIS VESSEL CONTAINS OXYGEN, U.S.P. (See reverse side for test results)
OXYGEN PRODUCED BY THE AIR LIQUEFACTION PROCESS

PRODUCT WARNINGS AND PRECAUTIONS

KEEP ALL OIL, GREASE, AND HYDROCARBONS AWAY. USE ONLY WITH EQUIPMENT DESIGNED AND CLEANED FOR OXYGEN SERVICE AND RATED FOR CYLINDER PRESSURE. OPEN VALVE SLOWLY AND CLOSE AFTER EACH USE. ALWAYS SECURE CYLINDER. STORE AND USE WITH ADEQUATE VENTILATION. USE A BACK FLOW PREVENTATIVE DEVICE IN THE PIPING. CYLINDER TEMPERATURE SHOULD NOT EXCEED 52 DEGREES C (125 DEGREES F) USE IN ACCORDANCE WITH RWS MSDS-OXY.

WARNING: FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS Rx ONLY.

WARNING: UNINTERRUPTED USE OF HIGH CONCENTRATIONS OF OXYGEN OVER A LONG DURATION, WITHOUT MONITORING ITS EFFECT ON OXYGEN CONTENT OF ARTERIAL BLOOD, MAY BE HARMFUL. USE ONLY WITH PRESSURE REDUCING

EQUIPMENT AND APPARATUS DESIGNED FOR OXYGEN. DO NOT ATTEMPT TO USE ON PATIENTS WHO HAVE STOPPED BREATHING UNLESS USED IN CONJUNCTION WITH RESUSCITATIVE EQUIPMENT.

DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:53828-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:53828-001-01	90 L in 1 CYLINDER		
2	NDC:53828-001-02	141 L in 1 CYLINDER		
3	NDC:53828-001-03	234 L in 1 CYLINDER		
4	NDC:53828-001-04	387 L in 1 CYLINDER		
5	NDC:53828-001-05	643 L in 1 CYLINDER		
6	NDC:53828-001-06	3172 L in 1 CYLINDER		
7	NDC:53828-001-07	6400 L in 1 CYLINDER		
8	NDC:53828-001-08	155223 L in 1 DEWAR		
9	NDC:53828-001-09	8522 L in 1 CYLINDER		
10	NDC:53828-001-10	1557 L in 1 CYLINDER		
11	NDC:53828-001-11	153864 L in 1 DEWAR		
12	NDC:53828-001-12	338870 L in 1 TANK		
13	NDC:53828-001-13	387762 L in 1 TANK		
14	NDC:53828-001-14	61911 L in 1 TANK		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/01/1935	

Labeler - Rochester Welding Supply Corp. (013133509)

Registrant - Rochester Welding Supply Corp. (013133509)

Establishment

Name	Address	ID/FEI	Business Operations
Rochester Welding Supply Corp.		013133509	manufacture

Revised: 1/2010

Rochester Welding Supply Corp.