

HELIOX- heliox gas
A-OX WELDING SUPPLY CO., INC.

Heliox 20/80

PurityPlus Specialty Gases by A-OX Welding Supply

Compressed gas, n.o.s. (Oxygen, Helium)

UN1956

PPG HEOX20K Part Number

Medical Gas Mixture

20 Percent Oxygen, USP CAS: 7782-44-7

Balance Helium, USP CAS: 7440-59-7

Rx only

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ACCIDENTLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL

For Medical Use Only.

Ver. 3.90

A-OX Welding Supply Co.

101 N. Harlem Ave.

Sioux Falls, SD 57104

605.336.1125



Compressed gas, n.o.s.
(Oxygen, Helium)

UN1956

PPG HEOX20K
Part Number

Medical Gas Mixture

20 % Oxygen, USP
Balance Helium, USP

CAS: 7782-44-7
CAS: 7440-59-7

See only

WARNING: Administration of this gas mixture may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of gas mixtures and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Close valves after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ACCIDENTLY INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention.

HELIOX

heliox gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:10297-007
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	200 mL in 1 L

Inactive Ingredients

Ingredient Name	Strength
HELIUM (UNII: 206GF3GB41)	800 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10297-007-01	637.13 L in 1 CYLINDER; Type 0: Not a Combination Product	06/01/2018	
2	NDC:10297-007-02	5810.62 L in 1 CYLINDER; Type 0: Not a Combination Product	06/01/2018	
3	NDC:10297-007-03	7744.66 L in 1 CYLINDER; Type 0: Not a Combination Product	06/01/2018	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205737	06/01/2018	

Labeler - A-OX WELDING SUPPLY CO., INC. (024372385)

Establishment

Name	Address	ID/FEI	Business Operations
A-OX WELDING SUPPLY CO., INC.		024372385	manufacture(10297-007)

Revised: 10/2021

A-OX WELDING SUPPLY CO., INC.