

HELIUM- helium gas
A-OX WELDING SUPPLY CO., INC.

Helium

HELIUM, COMPRESSED USP

UN1046

RX Only. WARNING: Administration of Helium may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Helium and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. CAS: 7440-59-7 DO NOT REMOVE THIS PRODUCT LABEL.

A-OX WELDING SUPPLY

PURITYPLUS Specialty Gases

101 N. HARLEM AVE.

SIOUX FALLS, SD 57104

605-336-1125

**HELIUM,
COMPRESSED
USP
UN1046**



37580 (04/17)

A-OX:PurityPlus
Welding Supply Specialty Gases

101 N. HARLEM AVE.
SIOUX FALLS, SD 57104
605-336-1125

Px Only. WARNING: Administration of Helium may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Helium and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.
WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. CAS: 7440-59-7. **DO NOT REMOVE THIS PRODUCT LABEL.**

Contents: _____
LITERS _____
CUBIC FEET _____

HELIUM

helium gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:10297-006
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
HELIUM (UNII: 206GF3GB41) (HELIUM - UNII:206GF3GB41)	HELIUM	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10297-006-01	85 L in 1 CYLINDER; Type 0: Not a Combination Product	06/01/2018	
2	NDC:10297-006-02	623 L in 1 CYLINDER; Type 0: Not a Combination Product	06/01/2018	
3	NDC:10297-006-03	6201 L in 1 CYLINDER; Type 0: Not a Combination Product	06/01/2018	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date

NDA	NDA211781	06/01/2018	
-----	-----------	------------	--

Labeler - A-OX WELDING SUPPLY CO., INC. (024372385)

Establishment

Name	Address	ID/FEI	Business Operations
A-OX WELDING SUPPLY CO., INC.		024372385	manufacture(10297-006)

Revised: 12/2024

A-OX WELDING SUPPLY CO., INC.