

**OXYGEN- oxygen gas**  
**MITCHELL WELDING SUPPLY**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52C (125F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.



OXYGEN, COMPRESSED USP

UN1072

PRODUCED BY AIR LIQUEFACTION

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER:**

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

MWS

Mitchell Welding Supply

3539 HIGHWAY 271

TYLER, TX 75708

903-593-7343



OXYGEN, COMPRESSED USP

UN1072

Produced by Air Liquefaction

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law required that this

container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.**

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

MWS

Mitchell Welding Supply

3539 HIGHWAY 271. TYLER, TX 75708

903-593-7343

<b>OXYGEN, COMPRESSED USP UN1072</b>		<b>MWS</b> 3539 HIGHWAY 271 • TYLER, TX 75708 903-593-7343
<b>Produced by Air Liquefaction</b>		
<b>WARNING:</b> For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, <b>do not</b> . Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.	Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.	
<b>DANGER:</b> MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.	CAS: 7782-44-7	
DO NOT REMOVE THIS PRODUCT LABEL.		

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:72276-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:72276-001-01	6909.31 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
2	NDC:72276-001-02	707.92 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
3	NDC:72276-001-03	396.44 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
4	NDC:72276-001-04	113 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
5	NDC:72276-001-05	172 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
6	NDC:72276-001-06	166 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
7	NDC:72276-001-07	211 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
8	NDC:72276-001-08	323 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
9	NDC:72276-001-09	233 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
10	NDC:72276-001-10	354 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
11	NDC:72276-001-11	605 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
12	NDC:72276-001-12	992 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
13	NDC:72276-001-13	250 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
14	NDC:72276-001-14	425 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
15	NDC:72276-001-15	510 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
16	NDC:72276-001-16	652 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
17	NDC:72276-001-17	679 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
18	NDC:72276-001-18	1702 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
19	NDC:72276-001-19	3454 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
20	NDC:72276-001-20	199 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
21	NDC:72276-001-21	214 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
22	NDC:72276-001-22	235 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	

23	NDC:72276-001-23	400 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
24	NDC:72276-001-24	427 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
25	NDC:72276-001-25	470 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
26	NDC:72276-001-26	651 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
27	NDC:72276-001-27	534 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
28	NDC:72276-001-28	587 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
29	NDC:72276-001-29	652 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
30	NDC:72276-001-30	697 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
31	NDC:72276-001-31	766 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
32	NDC:72276-001-32	1190 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
33	NDC:72276-001-33	1308 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
34	NDC:72276-001-34	1627 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
35	NDC:72276-001-35	1787 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
36	NDC:72276-001-36	2452 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
37	NDC:72276-001-37	2697 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
38	NDC:72276-001-38	3302 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
39	NDC:72276-001-39	3540 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
40	NDC:72276-001-40	4021 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
41	NDC:72276-001-41	4248 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
42	NDC:72276-001-42	5381 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
43	NDC:72276-001-43	5664 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
44	NDC:72276-001-44	7505 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
45	NDC:72276-001-45	6410 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
46	NDC:72276-001-46	7100 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
47	NDC:72276-001-47	7250 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
48	NDC:72276-001-48	7960 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
49	NDC:72276-001-49	8690 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
50	NDC:72276-001-50	9540 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
51	NDC:72276-001-51	11525 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	
52	NDC:72276-001-52	12652 L in 1 CYLINDER; Type 0: Not a Combination Product	07/05/2018	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205889	07/05/2018	

**Labeler** - MITCHELL WELDING SUPPLY (047833462)

## Establishment

Name	Address	ID/FEI	Business Operations
MITCHELL WELDING SUPPLY		047833462	manufacture(72276-001)

## Establishment

Name	Address	ID/FEI	Business Operations
MITCHELL WELDING SUPPLY		118920889	manufacture(72276-001)

Revised: 12/2024

MITCHELL WELDING SUPPLY