

**NITROUS OXIDE- nitrous oxide gas**  
**AGL Welding Supply Co., Inc.**

**nitrous oxide**

Nitrous Oxide, Refrigerated Liquid USP UN2201 NON-FLAMMABLE GAS 2 OXIDIZER 5.1  
AGL Certified ISO 9001:2008 Inhalation Therapy Co. 973-478-5100 600 RT. 46 WEST,  
CLIFTON, NJ 07015

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING: Rx only. Administration of Nitrous Oxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 10024-97-2 DO NOT REMOVE THIS LABEL.



NITROUS OXIDE, USP UN1070 NON-FLAMMABLE GAS 2 OXIDIZER 5.1  
Rx only. WARNING: Administration of Nitrous Oxide may be hazardous or

contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrous Oxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Avoid breathing gas. Do not put in eyes on skin or on clothing. Use and store only outdoors or in a well-ventilated place. In case of fire: stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 10024-97-2 DO NOT REMOVE THIS LABEL. Size: E Liters: 1,478 E AGL Certified ISO 9001:2008 Inhalation Therapy Co. 600 RT. 46 WEST, CLIFTON, NJ 07015 973-478-5100



## NITROUS OXIDE

nitrous oxide gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:17575-011
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
<b>NITROUS OXIDE</b> (UNII: K50XQU1029) (NITROUS OXIDE - UNII:K50XQU1029)	NITROUS OXIDE	990 mL in 1 L

## Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:17575-011-01	12320 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1966	
2	NDC:17575-011-02	4928 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1966	
3	NDC:17575-011-03	3696 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1966	
4	NDC:17575-011-04	2464 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1966	
5	NDC:17575-011-05	1478 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1966	
6	NDC:17575-011-06	99792 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1966	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA206009	01/01/1966	

**Labeler** - AGL Welding Supply Co., Inc. (011186004)

## Establishment

Name	Address	ID/FEI	Business Operations
AGL Welding Supply Co., Inc.		011186004	manufacture(17575-011)

Revised: 10/2023

AGL Welding Supply Co., Inc.