# NITROGEN- nitrogen gas A OX Welding Supply Company Inc.

-----

## Nitrogen

#### NITROGEN, COMPRESSED NF UN1066 NON-FLAMMABLE GAS 2

Rx only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9 DO NOT REMOVE THIS PRODUCT LABEL. CONTENTS: LTRS: CU FT: A-OX WELDING SUPPLY CO. 101 N. HARLEM AVE. . SIOUX FALLS, SD 57104 605-336-1125



NITROGEN REFRIGERATED LIQUID NF UN1977 NON-FLAMMABLE GAS 2 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING: Rx ONLY Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken.

WARNING: CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. DO NOT change or force fit connections. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. CAS: 7727-37-9

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL

A-OX WELDING SUPPLY CO. 101 N. HARLEM AVE. . SIOUX FALLS, SD 57104 605-336-1125



#### **NITROGEN**

nitrogen gas

### **Product Information**

Product TypePRESCRIPTION ANIMAL DRUGItem Code (Source)NDC:10297-012

Route of Administration RESPIRATORY (INHALATION)

## **Active Ingredient/Active Moiety**

Ingredient NameBasis of StrengthStrengthNitrogen (UNII: N762921K75) (Nitrogen - UNII:N762921K75)Nitrogen990 mL in 1 L

Packaging							
#	Item Code	Package Description	Marketing Start Date	Marketing End Date			
1	NDC:10297-012-01	5 L in 1 CYLINDER					
2	NDC:10297-012-02	10 L in 1 CYLINDER					
3	NDC:10297-012-03	18 L in 1 CYLINDER					
4	NDC:10297-012-04	20 L in 1 CYLINDER					
5	NDC:10297-012-05	160 L in 1 DEWAR					
6	NDC:10297-012-06	180 L in 1 DEWAR					
7	NDC:10297-012-07	200 L in 1 DEWAR					

Marketing Information								
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date					
NADA	NADA141359	01/09/2012						

# Labeler - A OX Welding Supply Company Inc. (024372385)

Establishment							
Name	Address	ID/FEI	Business Operations				
A OX Welding Supply Company Inc.		024372385	manufacture				

Revised: 1/2016 A OX Welding Supply Company Inc.