## OXYGEN- oxygen gas Life Supply Corp

-----

### Oxygen

# **Principal for Oxygen Product**



Representative Labeling pursuant to 21 CFR 207.3 (10)
Company name and contact information are printed in this box

**OXYGEN** 

**COMPRESSED** 

USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and

store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °c (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency


and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



Representative Labeling pursuant to 21 CFR 207.3 (10)



CONTENTS: LITERS 1 ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

AWARNING: DO NOT CHANGE OR FORCE FIT CONNECTIONS

EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER

PRESSURE

VIGOROUSLY ACCELERATES COMBUSTION.

NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY

EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Container temperature should not exceed 52°C (125°F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS). ▲FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

**△WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only.

> Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

DO NOT REMOVE THIS PRODUCT LABEL.

Representative Labeling pursuant to 21 CFR 207.3 (10) Company name and contact information are printed in this area

CAS NO: 7782-44-7

**REFRIGERATED** 

LIQUID USP

**UN 1073** 

CONTENTS LITERS

CAS NO: 7782-44-7

DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS
KEEP CONTAINER IN UPRIGHT POSITION. DO NOT
CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY
FIRE; OXIDIZER, CONTAINS REFRIGERATED GAS: MAY CAUSE
CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH
LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 F. Container temperature should not exceed 52 F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

#### FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water.

Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

# ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

## **OXYGEN**

oxygen gas

Product Information			
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:63553-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L	

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:63553- 001-01	164 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2019	
2	NDC:63553- 001-02	165 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2019	
3	NDC:63553- 001-03	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2019	
4	NDC:63553- 001-04	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2019	
5	NDC:63553- 001-05	1738 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2019	
6	NDC:63553- 001-06	3455 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2019	
7	NDC:63553- 001-07	7080 L in 1 CYLINDER; Type 0: Not a Combination Product	01/30/2019	
8	NDC:63553- 001-08	240 L in 1 DEWAR; Type 0: Not a Combination Product	01/30/2019	

Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/30/2019	

Establishment				
Name	Address	ID/FEI	Business Operations	
Life Supply Corp		176665412	manufacture(63553-001)	

Revised: 11/2024 Life Supply Corp