OXYGEN- oxygen gas Walnut Medical Services

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen, USP

Principal for Oxygen Product

OXYGEN, COMPRESSED USP UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. OXYGEN 2

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: No smoking or vaping. For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2023

Contents	Size
113 Liters	□ M4
165 Liters	□ M6
255 Liters	□С
425 Liters	□ D
680 Liters	□E
7080 Liters	□н
Liters	□ Other

CAS NO: 7782-44-7

Walnut Medical Services

226 Main St Johnstown PA 15901 814-533-0901

OXYGEN

COMPRESSED

USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY

EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °c (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7


DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency

and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



Do not handle until all safety precautions have been read and understood.

Keep and store away from dothing and other combustible materials.

Keep valves and fittings free from grease and oil.

Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face

shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: <u>Thaw frosted parts with lukewarm water. Do not rub affected</u> area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Supplied Home Healthcare Equipment 2014

Representative Labeling pursuant to 21 CFR 207.3 (10) Company name and contact information are printed in this area

OXYGEN,
REFRIGERATED
LIQUID USP
UN 1073
CONTENTS _____LITERS

CAS NO: 7782-44-7

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS
REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR
INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON
IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



Representative Labeling pursuant to 21 CFR 207.3 (10)

OXYGEN

oxygen gas

Product Information				
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:72739-001	
Route of Administration	RESPIRATORY (INHALATION)			

Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L	

P	Packaging			
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:72739-001- 01	164 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
2	NDC:72739-001- 02	425 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
3	NDC:72739-001- 03	680 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
4	NDC:72739-001- 04	41 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	
5	NDC:72739-001- 05	31 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	
6	NDC:72739-001- 06	21 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		05/01/2003	

Labeler - Walnut Medical Services (118301258)

Establishment					
Name	Address	ID/FEI	Business Operations		
Walnut Medical Services		118301258	manufacture(72739-001)		

Revised: 11/2024 Walnut Medical Services