

**OXYGEN- oxygen gas**  
**Fairmeadows Home Health Center**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

**Oxygen**

**Principal for Oxygen Product**

**OXYGEN,  
COMPRESSED USP  
UN 1072**

**DANGER:**  
MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.  
CONTAINS GAS UNDER PRESSURE;  
MAY EXPLODE IF HEATED.



Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

Contents	Size
113 Liters	<input type="checkbox"/> M4
165 Liters	<input type="checkbox"/> M6
255 Liters	<input type="checkbox"/> C
425 Liters	<input type="checkbox"/> D
680 Liters	<input type="checkbox"/> E
7080 Liters	<input type="checkbox"/> H
____ Liters	<input type="checkbox"/> Other

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2014

**Representative Labeling  
pursuant to 21 CFR 207.3 (10)  
Company name and contact information  
are printed in this box**

OXYGEN

COMPRESSED

USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from

clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °c (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency

and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**  
**UN 1073**



CONTENTS: \_\_\_\_\_ LITERS

**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑**

**△WARNING:** DO NOT CHANGE OR FORCE FIT CONNECTIONS  
EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER  
PRESSURE  
VIGOROUSLY ACCELERATES COMBUSTION.  
NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY  
EXPLODE ON IGNITION OR IMPACT.  
CAN CAUSE SEVERE FROSTBITE.  
Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Container temperature should not exceed 52°C (125°F).  
Close valve after each use and when empty.

**Use a back flow preventive device in the piping.**

Use in accordance with the Material Safety Data Sheet (MSDS).

**△FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

**△WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx Only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

**DO NOT REMOVE THIS PRODUCT LABEL.**

Representative Labeling  
pursuant to 21 CFR 207.3 (10)  
Company name and contact information  
are printed in this area

CAS NO: 7782-44-7

OXYGEN,

REFRIGERATED

LIQUID USP

UN 1073

CONTENTS \_\_\_\_\_ LITERS

CAS NO: 7782-44-7

DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS

KEEP CONTAINER IN UPRIGHT POSITION. DO NOT

CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY

FIRE; OXIDIZER, CONTAINS REFRIGERATED GAS: MAY CAUSE

CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH  
LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free

from grease and oil. In case of fire, stop leak if safe to do so. Avoid

spills. Do not walk or roll equipment over spills. Store and use in a well

ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 F. Container temperature should not exceed 52 F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

**FIRST AID:**

**IN CASE OF FROSTBITE:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**DO NOT REMOVE THIS PRODUCT LABEL.**

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION**

**LOT  
EXPIRATION DATE**

Representative Labeling  
pursuant to 21 CFR 207.3 (10)

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:67133-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

### Packaging

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:67133-001-01	113 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
2	NDC:67133-001-02	165 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
3	NDC:67133-001-04	255 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
4	NDC:67133-001-03	164 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
5	NDC:67133-001-05	425 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
6	NDC:67133-001-06	640 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
7	NDC:67133-001-07	680 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
8	NDC:67133-001-08	1738 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
9	NDC:67133-001-09	3455 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
10	NDC:67133-001-10	7080 L in 1 CYLINDER; Type 0: Not a Combination Product	05/05/2011	
11	NDC:67133-001-11	21 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	
12	NDC:67133-001-12	31 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	
13	NDC:67133-001-13	41 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	
14	NDC:67133-001-14	93 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	
15	NDC:67133-001-15	40 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	
16	NDC:67133-001-16	540 L in 1 DEWAR; Type 0: Not a Combination Product	05/05/2011	

### Marketing Information

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
unapproved medical gas		05/01/2003	

**Labeler** - Fairmeadows Home Health Center (039582392)

### Establishment

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Fairmeadows Home Health Center		039582392	manufacture(67133-001)

## Establishment

Name	Address	ID/FEI	Business Operations
Fairmeadows Home Health Center, Inc.		071972951	label(67133-001)

Revised: 10/2019

Fairmeadows Home Health Center