


OXYGEN- oxygen gas
UnityPoint at Home

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen

Principal for Oxygen Product

**OXYGEN,
REFRIGERATED
LIQUID USP**
UN 1073



CONTENTS: _____ LITERS

CAS NO: 7782-44-7

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

©Applied Home Healthcare Equipment 2014

Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information are
printed in this area

OXYGEN,

REFRIGERATED

LIQUID USP

UN 1073

CONTENTS _____ LITERS

CAS NO: 7782-44-7

DANGER:

REFRIGERATED LIQUEFIED OXIDIZING GAS. ALWAYS

KEEP CONTAINER IN UPRIGHT POSITION. DO NOT

CHANGE OR FORCE FIT CONNECTIONS. MAY CAUSE OR INTENSIFY

FIRE; OXIDIZER, CONTAINS REFRIGERATED GAS: MAY CAUSE

CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH

LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not get in eyes, on skin, or on clothing. Keep reduction valves free from grease and oil. In case of fire, stop leak if safe to do so. Avoid spills. Do not walk or roll equipment over spills. Store and use in a well ventilated place. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Wear cold insulating gloves/face shield/eye protection. Protect from sunlight when ambient temperature exceeds 52 F. Container temperature should not exceed 52 F. Close valve after each use and when empty. Use a back flow preventative device in the piping. Do not handle until all safety precautions have been read and understood. Use only with equipment cleaned for oxygen service. Keep/store away from combustible materials. Do not drop. Use suitable hand truck for container movement.

FIRST AID:

IN CASE OF FROSTBITE: Thaw frosted parts with lukewarm water.

Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

OXYGEN, COMPRESSED USP

UN 1072



DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: No smoking or vaping. For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2023

Contents	Size
113 Liters	<input type="checkbox"/> M4
165 Liters	<input type="checkbox"/> M6
255 Liters	<input type="checkbox"/> C
425 Liters	<input type="checkbox"/> D
680 Liters	<input type="checkbox"/> E
7080 Liters	<input type="checkbox"/> H
____ Liters	<input type="checkbox"/> Other

Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information are
printed in this box

OXYGEN
COMPRESSED

USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE;
OXIDIZER. CONTAINS GAS UNDER
PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °c (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: No smoking or vaping. For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2023

~~LOT~~
~~EXPIRATION DATE~~

Representative Labeling
pursuant to 21 CFR 207.3 (10)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:66698-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:66698-001-02	164 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
2	NDC:66698-001-01	165 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
3	NDC:66698-001-03	255 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
4	NDC:66698-001-04	425 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
5	NDC:66698-001-05	680 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
6	NDC:66698-001-06	1738 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
7	NDC:66698-001-07	3455 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
8	NDC:66698-001-08	7080 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2014	
9	NDC:66698-001-09	20 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	
10	NDC:66698-001-10	40 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	
11	NDC:66698-001-11	60 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	
12	NDC:66698-001-12	180 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	
13	NDC:66698-001-13	719 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	
14	NDC:66698-001-14	21 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	
15	NDC:66698-001-15	41 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	
16	NDC:66698-001-16	46 L in 1 DEWAR; Type 0: Not a Combination Product	10/01/2014	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
---------------------------	-------------------------------------------------	-----------------------------	---------------------------

unapproved medical gas		10/01/2014	
------------------------	--	------------	--

Labeler - UnityPoint at Home (151070955)

Establishment

Name	Address	ID/FEI	Business Operations
UnityPoint at Home		061943101	manufacture(66698-001)

Revised: 12/2024

UnityPoint at Home