

OXYGEN- oxygen gas
Badger Welding Supplies, Inc.

OXYGEN - 001

OXYGEN COMPRESSED USP LABEL

OXYGEN COMPRESSED USP

UN 1072

PRODUCED BY AIR LIQUEFACTION

OXYGEN 2

17033 (01/25)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx required.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of constructions. Open valve slowly. Use only with equipment cleaned for oxygen service. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

BADGER WELDING SUPPLIES, INC.

101 SOUTH DICKSON STREET MADISON WI 53703

608-257-5606

CONTENTS: LTRS. _____ CU. FT. _____

NO SMOKING

NO VAPING

OXYGEN,
COMPRESSED
USP
UN1072
PRODUCED BY AIR LIQUEFACTION



17033 (01/25)
WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx required.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless it is in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR WITNESS FIRE.** OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire, stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment cleaned for oxygen service. Protect from sunlight when slowly. Use only with equipment cleaned for oxygen service. Read and follow the Safety Data Sheet (SDS) before use. ambient temperature exceeds 32°C (125°F). **DO NOT REMOVE THIS PRODUCT LABEL.**
use: CAS 7782-44-7

BADGER WELDING SUPPLIES, INC.
101 SOUTH DICKINSON STREET • MADISON, WI 53703
609-257-5606

CONTENTS: LTRS. CU. FT.
NO SMOKING
NO VAPING

OXYGEN,
COMPRESSED
USP
UN1072
PRODUCED BY AIR LIQUEFACTION



17033 (01/25)
WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx required.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless it is in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR WITNESS FIRE.** OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire, stop leak if safe to do so. Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment cleaned for oxygen service. Protect from sunlight when slowly. Use only with equipment cleaned for oxygen service. Read and follow the Safety Data Sheet (SDS) before use. ambient temperature exceeds 32°C (125°F). **DO NOT REMOVE THIS PRODUCT LABEL.**
use: CAS 7782-44-7

BADGER WELDING SUPPLIES, INC.
101 SOUTH DICKINSON STREET • MADISON, WI 53703
609-257-5606

CONTENTS: LTRS. CU. FT.
NO SMOKING
NO VAPING

OXYGEN REFRIGERATED LIQUID USP LABEL
REFRIGERATED LIQUID
OXYGEN REFRIGERATED LIQUID USP

UN 1073
OXYGEN 2

CONTENTS: _____ LTRS: _____ CU. FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx Only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless it is in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS: MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advise/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

BADGER WELDING SUPPLIES, INC.
101 SOUTH DICKSON STREET • MADISON, WI 53703

608-257-5606

47136 (03/17)

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP
UN1073**



CONTENTS: _____

LTRS:

CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food, Drug, and Cosmetic Act*.
Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL



BADGER WELDING SUPPLIES, INC.
101 SOUTH DICKINSON STREET • MADISON, WI 53703
608-257-5606

47136
(03/17)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:12121-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:12121-001-01	141 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1955	
2	NDC:12121-001-02	234 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1955	
3	NDC:12121-001-03	387 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1955	
4	NDC:12121-001-04	643 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1955	
5	NDC:12121-001-05	1738 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1955	
6	NDC:12121-001-06	3511 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1955	
7	NDC:12121-001-07	7051 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1955	
8	NDC:12121-001-09	127400 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1955	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1955	

Labeler - Badger Welding Supplies, Inc. (023314099)

Registrant - Badger Welding Supplies, Inc. (023314099)

Establishment

Name	Address	ID/FEI	Business Operations
-------------	----------------	---------------	----------------------------

Badger Welding Supplies, Inc.		023314099	manufacture(12121-001)
-------------------------------	--	-----------	------------------------

Revised: 7/2025

Badger Welding Supplies, Inc.