OXYGEN- oxygen gas Inland Welding Supply dba A-L Compressed Gases

Oxygen liquid label

OXYGEN, COMPRESSED USP UN1072

Produced by Air Liquefaction

WARNING: For emergency use only when administered by personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fitting free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (0) before use.

NET CONTENTS

CYLINDER TYPE LITERS

T 9310

K 6900

S 4250

D,E,Y 3500

Q 2320

XL 1970

AN-E 625

AN-D 360

R 570

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

A-L COMPRESSED GASES, INC.

4230 E. TRENT AVE. SPOKANE, WA 99202

1-800-852-4979



OXYGEN, COMPRESSED USP UN1072

Produced by Air Liquefaction

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7
DO NOT REMOVE THIS PRODUCT LABEL.
A-L COMPRESSED GASES, INC.
4230 E. TRENT AVE.
SPOKANE, WA 99202
1-800-852-4979



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.


DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL. A-L COMPRESSED GASES, INC. 4230 E. TRENT AVE. SPOKANE, WA 99202 1-800-852-4979



OXYGEN, COMPRESSED USP UN1072 PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a wellventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only equipment cleaned for oxygen service. Open valve slowly. Close valve after use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

A-L COMPRESSED GASES, INC.

4230 E. TRENT AVE. SPOKANE, WA 99202 1-800-852-4979




OXYGEN, COMPRESSED USP UN1072

Produced by Air Liquefaction

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



OXYGEN, COMPRESSED USP UN1072

Produced by Air Liquefaction

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Read and follow the Safety Data Sheet (SDS0 before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

A-L COMPRESSED GASES, INC.

4230 E. TRENT AVE. SPOKANE, WA 99202







WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for oxygen service. Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.



A-L COMPRESSED GASES, INC.

4230 E. TRENT AVE. • SPOKANE, WA 99202 1-800-852-4979

OXYGEN

oxygen gas

Product Information				
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:18482-018	
Route of Administration	RESPIRATORY (INHALATION)			

Active Ingredient/Active Moiety				
Ingredient Name	Basis of Strength	Strength		
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L		

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:18482- 018-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
2	NDC:18482- 018-02	255 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
2	NDC:18482-	425 L in 1 CYLINDER; Type 0: Not a Combination	07/01/2005	

3	018-03	Product	07/01/2005	
4	NDC:18482- 018-04	708 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
5	NDC:18482- 018-05	595 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
6	NDC:18482- 018-06	9429 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
7	NDC:18482- 018-07	8693 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
8	NDC:18482- 018-08	7107 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
9	NDC:18482- 018-09	6456 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
10	NDC:18482- 018-10	648 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
11	NDC:18482- 018-11	1132 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
12	NDC:18482- 018-12	2265 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
13	NDC:18482- 018-13	3539 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
14	018-14	4389 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
	NDC:18482- 018-15	7957 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
16	NDC:18482- 018-16	4530 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2005	
	NDC:18482- 018-17	5097 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2005	
18	NDC:18482- 018-18	5663 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2005	

Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA206023	07/01/2005	

Labeler - Inland Welding Supply dba A-L Compressed Gases (620529529)

Establishment					
Name	Address	ID/FEI	Business Operations		
A-L Compressed Gases		620529529	manufacture(18482-018)		

Revised: 6/2024 Inland Welding Supply dba A-L Compressed Gases