

**OXYGEN- oxygen gas**  
**Southern Gas and Supply LLC**

-----  
**Oxygen Label**

OXYGEN, COMPRESSED USP UN1072  
OXYGEN 2

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for use with oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUEFACTION.

**WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52C (125F). Use in accordance with Material Safety Data Sheet (MSDS).


**DO NOT REMOVE THIS PRODUCT LABEL.**

**GAS AND SUPPLY**

3945 EAST LAKE BLVD BIRMINGHAM, AL 35217 205-849-5947

UN1072

CONTENTS: LTRS: CU.FT.



OXYGEN, REFRIGERATED LIQUID  
USP

UN1073 OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

CONTENTS:

LOT #:

**WARNING:**For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without

monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATED COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.**

Keep oil, grease and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

**FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.**

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**GAS AND SUPPLY**

**3945 EAST LAKE BLVD**

**BIRMINGHAM, AL 35217**

# OXYGEN, REFRIGERATED LIQUID

## USP



## UN1073

**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑**

CONTENTS: \_\_\_\_\_

LOT #: \_\_\_\_\_

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**WARNING:** EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52°C (125°F).  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the Material Safety Data Sheet (MSDS).

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**GAS AND SUPPLY**  
3945 EAST LAKE BLVD.  
BIRMINGHAM, AL 35217  
205-849-5947

205-849-5947

**OXYGEN**

oxygen gas

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:76349-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	995 mL in 1 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:76349-001-01	198 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
2	NDC:76349-001-02	425 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
3	NDC:76349-001-03	708 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
4	NDC:76349-001-04	3228 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
5	NDC:76349-001-05	3540 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
6	NDC:76349-001-06	6456 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
7	NDC:76349-001-07	7108 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
8	NDC:76349-001-08	7249 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
9	NDC:76349-001-09	7957 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
10	NDC:76349-001-10	8693 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
11	NDC:76349-001-11	9543 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2011	
12	NDC:76349-001-12	180 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2011	
13	NDC:76349-001-13	200 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2011	

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
NDA	NDA205767	07/01/2011	

**Labeler** - Southern Gas and Supply LLC (002164525)**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
-------------	----------------	---------------	----------------------------

Revised: 10/2024

Southern Gas and Supply LLC