

CARBON DIOXIDE- carbon dioxide gas
A-OX WELDING SUPPLY CO., INC.

Carbon Dioxide

CARBON DIOXIDE USP

UN1013

Rx only. WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE.

Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS 124-38-9 DO NOT REMOVE THIS PRODUCT LABEL.


A-OX Welding Supply

PurityPlus Specialty Gases

101 N. HARLEM AVE.

SIOUX FALLS, SD 57104

605-336-1125



CARBON DIOXIDE USP

UN1013

Rx only. WARNING: Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE.

Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS 124-38-9

DO NOT REMOVE THIS PRODUCT LABEL.

A-OX Welding Supply

PurityPlus Specialty Gases

101 N. HARLEM AVE.

SIOUX FALLS, SD 57104

605-336-1125

CARBON DIOXIDE
USP

UN1013



For use only. **WARNING:** Administration of Carbon Dioxide may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Carbon Dioxide and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.
WARNING: CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY CAUSE FROSTBITE. MAY INCREASE RESPIRATION AND HEART RATE.
Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.
FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS 124-38-9

DO NOT REMOVE THIS PRODUCT LABEL.

A-OX **PurityPlus**
Welding Supply Specialty Gases
101 N. HARLEM AVE. • SIOUX FALLS, SD 57104
605-336-1125

40036
(03/19)

CARBON DIOXIDE

carbon dioxide gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:10297-020
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
CARBON DIOXIDE (UNII: 142M471B3J) (CARBON DIOXIDE - UNII:142M471B3J)	CARBON DIOXIDE	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10297-020-01	1683 L in 1 CYLINDER; Type 0: Not a Combination Product	06/17/2019	
2	NDC:10297-020-02	12375 L in 1 CYLINDER; Type 0: Not a Combination Product	06/17/2019	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA213507	06/17/2019	

Labeler - A-OX WELDING SUPPLY CO., INC. (024372385)

Establishment

Name	Address	ID/FEI	Business Operations
A-OX WELDING SUPPLY CO., INC.		024372385	manufacture(10297-020)

Revised: 12/2024

A-OX WELDING SUPPLY CO., INC.