

OXYGEN- oxygen gas
Crompton Welding Supply & Equipment, Inc.

Oxygen

OXYGEN COMPRESSED LABEL

OXYGEN, COMPRESSED USP UN 1072 Produced by Air Liquefaction OXYGEN 2 17033 (03/17)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a backflow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTENTS:

LTRS: ____

CU.FT. ____

In case of emergency involving this material call INFOTRAC at 1-800-535-5063

CRUMPTON WELDING SUPPLY & EQUIPMENT, INC.

1602 N 34TH STREET • TAMPA, FL 33605 • 800-229-6947



REFRIGERATED LIQUID LABEL

REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP UN1073

OXYGEN 2

CONTENTS: _____ LTRS: ___ CU.FT. ___

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the *Federal Food, Drug, and Cosmetic Act*.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBELS IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID FIRST AID: IF ON SKIN: Thaw affected parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

In case of emergency involving this material call INFOTRAC at 1-800-535-5063

CRUMPTON WELDING SUPPLY & EQUIPMENT, INC.

1602 N 34TH STREET • TAMPA, FL 33605 • 800-229-6947

47136 (01/15)



REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN1073



CONTENTS: _____

LTRS:

CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R_x only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food, Drug, and Cosmetic Act*.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with

equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
CAS: 7782-44-7



DO NOT REMOVE THIS PRODUCT LABEL

In case of emergency involving this material call INFOTRAC at 1-800-535-5053

CRUMPTON WELDING SUPPLY & EQUIPMENT, INC.

1602 N 34TH STREET • TAMPA, FL 33605 • 800-229-6947

47136
(01/15)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:52568-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:52568-001-01	240 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
2	NDC:52568-001-02	400 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
3	NDC:52568-001-03	660 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
4	NDC:52568-001-04	3450 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
5	NDC:52568-001-05	5300 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	

6	NDC:52568-001-06	7100 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
7	NDC:52568-001-07	7960 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	
8	NDC:52568-001-08	12744 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1990	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205889	01/01/1990	

Labeler - Crumpton Welding Supply & Equipment, Inc. (067210450)

Registrant - Crumpton Welding Supply & Equipment, Inc. (067210450)

Establishment

Name	Address	ID/FEI	Business Operations
Crumpton Welding Supply & Equipment, Inc.		067210450	manufacture(52568-001)

Revised: 10/2023

Crumpton Welding Supply & Equipment, Inc.