

OXYGEN- oxygen gas
AGL Welding Supply CO., Inc.

oxygen

Produced by Air Liquefaction

OXYGEN, COMPRESSED USP UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx REQUIRED. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood.

Keep away from clothing and other combustible materials.

Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place.

In case of fire: Stop leak if safe to do so.

Use a back flow preventive device in the piping. Close valve after each use and when empty.

Use only with equipment rated for cylinder pressure.

Do not open valve until connected to equipment prepared for use. Use only equipment of compatible materials of construction.

Open valve slowly.

Use only with equipment cleaned for oxygen service.

Protect from sunlight when ambient temperature exceeds 52 C (125 F).

Read and follow the Safety Data Sheet (SDS) before use.

Manufactured by:

AGL

CERTIFIED ISO 9001

AGL Inhalation Therapy Co.

600 Route 46 West

Clifton, NJ 07015

NJ Tel: 973-478-5000

NY Tel: 845-561-5900

CAS 7782-44-7

NO SMOKING

NO VAPING

DO NOT REMOVE THIS PRODUCT LABEL

Produced by Air Liquefaction

**OXYGEN,
COMPRESSED
USP UN1072**



Manufactured by:

AGL
CERTIFIED ISO 9001



AGL Inhalation Therapy Co.
600 Route 46 West
Clifton, NJ 07015
NJ Tel: 973-478-5000
NY Tel: 845-561-5900

CAS 7782-44-7

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R** **REQUIRED**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

- Do not handle until all safety precautions have been read and understood.
- Keep away from clothing and other combustible materials.
- Keep valves and fittings free from grease and oil.
- Use and store only outdoors or in a well-ventilated place.
- In case of fire: Stop leak if safe to do so.
- Use a back flow preventive device in the piping.
- Close valve after each use and when empty.
- Use only with equipment rated for cylinder pressure.
- Do not open valve until connected to equipment prepared for use.
- Use only equipment of compatible materials of construction.
- Open valve slowly.
- Use only with equipment cleaned for oxygen service.
- Protect from sunlight when ambient temperature exceeds 52°C (125°F).
- Read and follow the Safety Data Sheet (SDS) before use.

**NO SMOKING
NO VAPING**



**DO NOT REMOVE
THIS PRODUCT LABEL**

AGL-8-D-241-4 (R 02/25)

OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:17575-021
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:17575-021-01	9540 L in 1 CYLINDER		
2	NDC:17575-021-02	7100 L in 1 CYLINDER		
3	NDC:17575-021-03	4390 L in 1 CYLINDER		
4	NDC:17575-021-04	3540 L in 1 CYLINDER		
5	NDC:17575-021-05	2350 L in 1 CYLINDER		
6	NDC:17575-021-06	566 L in 1 CYLINDER		
7	NDC:17575-021-07	660 L in 1 CYLINDER		
8	NDC:17575-021-08	400 L in 1 CYLINDER		
9	NDC:17575-021-09	170 L in 1 CYLINDER		

10	NDC:17575-021-10	127440 L in 1 DEWAR		
11	NDC:17575-021-11	141940 L in 1 DEWAR		
12	NDC:17575-021-12	172752 L in 1 DEWAR		
13	NDC:17575-021-13	38657 L in 1 DEWAR		
14	NDC:17575-021-14	210 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141365	01/01/1966	

Labeler - AGL Welding Supply CO., Inc. (011186004)

Establishment

Name	Address	ID/FEI	Business Operations
AGL Welding Supply CO., Inc.		011186004	manufacture

Revised: 10/2025

AGL Welding Supply CO., Inc.