-----

#### oxygen

# OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

Pressure: PSIG: @ 70 degrees F. Size: Liters:

AGL Certified ISO 9001:2008 Inhalation Therapy Co. 600 RT. 46 WEST, CLIFTON, NJ 07015 973-478-5100



#### OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

AGL Certified ISO 9001:2008 Inhalation Therapy Co. 973-478-5100 600 RT. 46 WEST, CLIFTON, NJ 07015

### ALWAYS KEEP CONTAINER IN UPRIGH POSITION

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. Keep out of reach of children. Federal law requires that this container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions

have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. DO NOT REMOVE THIS PRODUCT LABEL. CAS: 7782-44-7



# **OXYGEN**

oxygen gas

Product Information				
Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:17575-021	
Route of Administration	RESPIRATORY (INHALATION)			

Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L	

Packaging					
#	Item Code	Package Description	Marketing Start Date	Marketing End Date	
1	NDC:17575-021-01	9540 L in 1 CYLINDER			
2	NDC:17575-021-02	7100 L in 1 CYLINDER			
3	NDC:17575-021-03	4390 L in 1 CYLINDER			
4	NDC:17575-021-04	3540 L in 1 CYLINDER			
5	NDC:17575-021-05	2350 L in 1 CYLINDER			

	566 L in 1 CYLINDER		
DC:17575-021-07	CCC I I A CUI DIDED		
	660 L in 1 CYLINDER		
DC:17575-021-08	400 L in 1 CYLINDER		
DC:17575-021-09	170 L in 1 CYLINDER		
DC:17575-021-10	127440 L in 1 DEWAR		
DC:17575-021-11	141940 L in 1 DEWAR		
DC:17575-021-12	172752 L in 1 DEWAR		
DC:17575-021-13	38657 L in 1 DEWAR		
DC:17575-021-14	210 L in 1 CYLINDER		
	DC:17575-021-09 DC:17575-021-10 DC:17575-021-11 DC:17575-021-12 DC:17575-021-13	DC:17575-021-09 170 L in 1 CYLINDER DC:17575-021-10 127440 L in 1 DEWAR DC:17575-021-11 141940 L in 1 DEWAR DC:17575-021-12 172752 L in 1 DEWAR DC:17575-021-13 38657 L in 1 DEWAR	DC:17575-021-09 170 L in 1 CYLINDER  DC:17575-021-10 127440 L in 1 DEWAR  DC:17575-021-11 141940 L in 1 DEWAR  DC:17575-021-12 172752 L in 1 DEWAR  DC:17575-021-13 38657 L in 1 DEWAR

Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141365	0 1/0 1/19 6 6	

# Labeler - AGL Inhalation Therapy Co. (011186004)

Establishment				
Name	Address	ID/FEI	Business Operations	
AGL Inhalation Therapy Co.		011186004	manufacture	

Revised: 1/2016 AGL Inhalation Therapy Co.