

OXYGEN- oxygen gas
Jayco Industrial Supply Inc

Oxygen

OXYGEN, COMPRESSED USP. OXYGEN 2. UN 1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil, grease and combustibles away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 C (125 F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

JAYCO

GAS AND SUPPLY

2028 Natchez Dr

McComb, MS 39648

(601) 684-2154



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID. OXYGEN 2.

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away. Use only with equipment cleaned for oxygen

service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 C (125 F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: OXYGEN 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

JAYCO

GAS AND SUPPLY

2028 Natchez Dr

McComb, MS 39648

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID**



UN1073

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS
UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION.
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN
MAY EXPLODE ON IGNITION OR IMPACT.
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container
movement.
Avoid spills. Do not walk on or roll equipment over spills.
Cylinder temperature should not exceed 52C (125F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the **Material Safety Data Sheet
(MSDS)**.

FIRST AID: **IN CASE OF FROSTBITE**, obtain medical treatment
immediately.

CAS: OXYGEN 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

Jayco

**GAS AND
SUPPLY**

2028 Natchez Dr
McComb, MS 39648
(601) 684-2154

45131
(R 1204)

(601) 684-2154

OXYGEN

oxygen gas

Product Information

Product Type		HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:59378-001
Route of Administration		RESPIRATORY (INHALATION)		
Active Ingredient/Active Moiety				
Ingredient Name			Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)			OXYGEN	995 mL in 1 L
Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:59378-001-01	198 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
2	NDC:59378-001-02	425 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
3	NDC:59378-001-03	708 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
4	NDC:59378-001-04	3228 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
5	NDC:59378-001-05	3540 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
6	NDC:59378-001-06	6456 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
7	NDC:59378-001-07	7108 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
8	NDC:59378-001-08	7249 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
9	NDC:59378-001-09	7957 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
10	NDC:59378-001-10	8693 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
11	NDC:59378-001-11	9543 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2013	
12	NDC:59378-001-12	180 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2013	
13	NDC:59378-001-13	200 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2013	
Marketing Information				
Marketing Category		Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA		NDA205767	07/01/2013	

Labeler - Jayco Industrial Supply Inc (177843679)

Establishment

Name	Address	ID/FEI	Business Operations
Jayco Industrial Supply Inc		177843679	manufacture(59378-001)

