

**OXYGEN- oxygen gas**  
**Jackson Welding Supply Company, Inc**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.*

-----  
**OXYGEN COMPRESSED USP label**

**OXYGEN COMPRESSED USP**

**UN1072 OXYGEN 2**

**Produced by Air Liquefaction**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitations. For all other applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacture in accordance with the *Federal Food, Drug, and Cosmetic Act*.

**DANGER:**MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (0) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

**JACKSON WELDING SUPPLY CO. INC.**

1421 W. CARSON STREET • PITTSBURG, PA 15219 • 412-391-4500

IN CASE OF CHEMICAL EMERGENCY, CALL CHEMTREC AT 1-800-424-9300

40035 (01/15)

**OXYGEN,  
COMPRESSED  
USP**

**UN1072**



UN1072



Produced by Air Liquefaction

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food, Drug, and Cosmetic Act*.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (0) before use.

CAS: 7782-44-7



DO NOT REMOVE THIS PRODUCT LABEL.

**JACKSON WELDING SUPPLY CO., INC.**

1421 W. CARSON STREET • PITTSBURGH, PA 15219 • 412-391-4500  
IN CASE OF CHEMICAL EMERGENCY, CALL CHEMTREC AT 1-800-424-9300 40035  
(01/15)

res

**OXYGEN REFRIGERATED LIQUID LABEL**

**OXYGEN COMPRESSED UOXYGEN REFRIGERATED LIQUID USP UN1073**

**CONTENTS \_\_\_\_\_ LITERS ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

**WARNING: DO NOT CHANGE OR FORCE FIT CONNECTIONS. EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. NO SMOKING IN THE PRESENCE OF OXYGEN OR A FIRE MAY RESULT. COMBUSTIBLES**

**IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. KEEP OIL, GREASE AND COMBUSTIBLES AWAY. USE ONLY WITH EQUIPMENT CLEANED FOR OXYGEN SERVICE. STORE AND USE WITH ADEQUATE VENTILATION. DO NOT GET LIQUID IN EYES, ON SKIN OR CLOTHING. FOR LIQUID WITHDRAWAL, WEAR FACE SHIELD AND GLOVES. DO NOT DROP. USE SUITABLE HAND TRUCK FOR CONTAINER MOVEMENT. AVOID SPILLS. DO NOT WALK OR ROLL EQUIPMENT OVER SPILLS CONTAINER TEMPERATURE SHOULD NOT EXCEED 52C (125 F) CLOSE VALVE AFTER EACH USE AND WHEN EMPTY. USE A BACK FLOW PREVENTATIVE DEVICE IN THE PIPING. USE IN ACCORDANCE WITH THE MATERIAL SAFETY DATA SHEET (MSDS)**

**FIRST AID: IN CASE OF FROSTBITE OBTAIN MEDICAL TREATMENT IMMEDIATELY.**

**WARNING: FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS R<sub>x</sub> ONLY. UNINTERRUPTED USE OF HIGH CONCENTRATIONS OF OXYGEN OVER A LONG DURATION WITHOUT MONITORING ITS EFFECT ON OXYGEN CONTENT OF ARTERIAL BLOOD MAY BE HARMFUL. USE ONLY WITH PRESSURE REDUCING EQUIPMENT AND APPARATUS DESIGNED FOR OXYGEN. DO NOT ATTEMPT TO USE ON PATIENTS WHO HAVE STOPPED BREATHING, UNLESS USED IN CONJUNCTION WITH RESUSCITATIVE EQUIPMENT. PRODUCED BY AIR LIQUEFACTION. DO NOT REMOVE THIS PRODUCT LABEL.**

# **OXYGEN**

## **REFRIGERATED LIQUID, U.S.P.**

### **UN 1073**

**(CRYOGENIC LIQUID)**

Produced by Air Liquefaction



**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.**

#### **WARNING**

**WARNING!**  
EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX only.

WARNING: Caution Federal Law Prohibits Dispensing without Prescription.

**WARNING!**  
Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use in accordance with Material Safety Data Sheet.

#### **FIRST AID**

**IN CASE OF FROSTBITE, obtain medical treatment immediately.**

**PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.**

Company Name:

Lot Number:

Contents:

Expiration Date:



**DO NOT REMOVE THIS PRODUCT LABEL**

PART 408-USP  
PRINTED BY RATERMANN MFG INC. 925-600-2049

**OXYGEN**

oxygen gas

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:10590-0001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

**Packaging**

<b>#</b>	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:10590-0001-1	426 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1944	
2	NDC:10590-0001-2	671 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1944	
3	NDC:10590-0001-3	3462 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1944	
4	NDC:10590-0001-4	7981 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1944	
5	NDC:10590-0001-5	160 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1944	
6	NDC:10590-0001-6	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1944	
7	NDC:10590-0001-7	200 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1944	

**Marketing Information**

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
unapproved medical gas		01/01/1944	

**Labeler** - Jackson Welding Supply Company, Inc (001907708)**Registrant** - Jackson Welding Supply Company, Inc (001907708)**Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
Jackson Welding Supply Company, Inc		001907708	manufacture(10590-0001)